



**Description:** HITRONIC HDM Cable\_  
**Lapp code:** Lapp 26610408

The **Test voltage** of the cable Lapp 26610408 is /.

## Application range

- For flexible applications
- In temporary installations
- Industrial environments
- For indoor and outdoor use

## Product Make-up

- Up to 12 tight-buffered fibres (900µm)
- Aramid yarns as strain relief
- PUR outer sheath
- Colour: black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 26610408 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Fibre type	Number of fibres	Outer diameter (mm)	Weight (kg/km)
Multimode G 50 OM4						
HITRONIC HDM Cable	Lapp 26610404	HITRONIC® HDM600 4G 50/125 OM4	50/125 OM4	4	5.5	24
HITRONIC HDM Cable	Lapp 26610406	HITRONIC® HDM600 6G 50/125 OM4	50/125 OM4	6	5.6	29
HITRONIC HDM Cable	Lapp 26610408	HITRONIC® HDM700 8G 50/125 OM4	50/125 OM4	8	6.2	36
Multimode G 50 OM3						
HITRONIC HDM Cable	Lapp 26610304	HITRONIC® HDM600 4G 50/125 OM3	50/125 OM3	4	5.5	24
HITRONIC HDM Cable	Lapp 26610306	HITRONIC® HDM600 6G 50/125 OM3	50/125 OM3	6	5.6	29
HITRONIC HDM Cable	Lapp 26610308	HITRONIC® HDM700 8G 50/125 OM3	50/125 OM3	8	6.2	36
Multimode G 50 OM2						
HITRONIC HDM Cable	Lapp 26610204	HITRONIC® HDM600 4G 50/125 OM2	50/125 OM2	4	5.5	24
HITRONIC HDM Cable	Lapp 26610206	HITRONIC® HDM600 6G 50/125 OM2	50/125 OM2	6	5.6	29
HITRONIC HDM Cable	Lapp 26610208	HITRONIC® HDM700 8G 50/125 OM2	50/125 OM2	8	6.2	36
Multimode G 62.5 OM1						
HITRONIC HDM Cable	Lapp 26610104	HITRONIC® HDM600 4G 62.5/125 OM1	62.5/125 OM1	4	5.5	24
HITRONIC HDM Cable	Lapp 26610106	HITRONIC® HDM600 6G 62.5/125 OM1	62.5/125 OM1	6	5.6	29
HITRONIC HDM Cable	Lapp 26610108	HITRONIC® HDM700 8G 62.5/125 OM1	62.5/125 OM1	8	6.2	36