



Description: HITRONIC HMDC Micro Cable_

Lapp code: Lapp 27009802

The **Test voltage** of the cable Lapp 27009802 is /.

Application range

- FTTH applications
- House connection
- Telecommunications network
- For installations by blowing
- Methods of deployment: for blowing or pulling into micro ducts

Product Make-up

- Central mini subunit with up to 12 fibres
- Standard with single-mode fibre type G.657.A1 (low macrobending sensitive fibre)
- Aramid yarns as strain relief
- PE outer sheath
- Colour: black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 27009802 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Fibre type	Number of fibres	Outer diameter (mm)	Weight (kg/km)
HITRONIC HMDC Micro Cable	Lapp 27009802	HITRONIC® HMDC 2E9/125 G.657.A1	9/125 G.657.A1	2	2.0	5
HITRONIC HMDC Micro Cable	Lapp 27009804	HITRONIC® HMDC 4E9/125 G.657.A1	9/125 G.657.A1	4	2.0	5
HITRONIC HMDC Micro Cable	Lapp 27009806	HITRONIC® HMDC 6E9/125 G.657.A1	9/125 G.657.A1	6	2.2	5
HITRONIC HMDC Micro Cable	Lapp 27009808	HITRONIC® HMDC 8E9/125 G.657.A1	9/125 G.657.A1	8	2.3	5
HITRONIC HMDC Micro Cable	Lapp 27009812	HITRONIC® HMDC 12E9/125 G.657.A1	9/125 G.657.A1	12	2.5	5