



Description: HITRONIC HQW Armoured Outdoor Cable_
Lapp code: Lapp 27900212

The **Test voltage** of the cable Lapp 27900212 is /.

Application range

- For outdoor use
- Campus backbone
- WAN applications
- Industrial environments
- Methods of Deployment: empty plastic pipes, ducts and trays

Product Make-up

- Gel-filled loose tube
- Water-blocking reinforced glass yarn strain relief
- Corrugated steel tape armour
- PE outer sheath
- Colour: black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 27900212 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Fibre type	Number of fibres	Outer diameter (mm)	Weight (kg/km)
Multimode G 50 OM3						
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900304	HITRONIC® HQW3000 4G 50/125 OM3	50/125 OM3	4	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900308	HITRONIC® HQW3000 8G 50/125 OM3	50/125 OM3	8	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900312	HITRONIC® HQW3000 12G 50/125 OM3	50/125 OM3	12	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900324	HITRONIC® HQW3000 24G 50/125 OM3	50/125 OM3	24	9.6	88
Multimode G 50 OM2						
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900204	HITRONIC® HQW3000 4G 50/125 OM2	50/125 OM2	4	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900208	HITRONIC® HQW3000 8G 50/125 OM2	50/125 OM2	8	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900212	HITRONIC® HQW3000 12G 50/125 OM2	50/125 OM2	12	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900224	HITRONIC® HQW3000 24G 50/125 OM2	50/125 OM2	24	9.6	88
Multimode G 62.5 OM1						
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900104	HITRONIC® HQW3000 4G 62.5/125 OM1	62.5/125 OM1	4	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900108	HITRONIC® HQW3000 8G 62.5/125 OM1	62.5/125 OM1	8	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900112	HITRONIC® HQW3000 12G 62.5/125 OM1	62.5/125 OM1	12	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900124	HITRONIC® HQW3000 24G 62.5/125 OM1	62.5/125 OM1	24	9.6	88
Single-mode E 9 OS2						
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900904	HITRONIC® HQW3000 4E 9/125 OS2	9/125 OS2	4	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900908	HITRONIC® HQW3000 8E 9/125 OS2	9/125 OS2	8	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900912	HITRONIC® HQW3000 12E 9/125 OS2	9/125 OS2	12	9.6	88
HITRONIC HQW Armoured Outdoor Cable	Lapp 27900924	HITRONIC® HQW3000 24E 9/125 OS2	9/125 OS2	24	9.6	88