



Description: HITRONIC HQW-Plus Armoured Outdoor Cable_

Lapp code: Lapp 27920304

The **Test voltage** of the cable Lapp 27920304 is /.

Application range

- For outdoor use
- Harsh industrial environment
- Campus backbone
- WAN applications
- Methods of Deployment: empty plastic pipes, ducts and trays

Product Make-up

- Gel-filled loose tube
- Water-blocking reinforced glass yarn strain relief
- Corrugated steel tape armour
- PE inner and outer sheaths
- Colour: black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 27920304 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Fibre type	Number of fibres	Outer diameter (mm)	Weight (kg/km)
Multimode G 50 OM3						
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920304	HITRONIC® HQW-Plus3000 4G 50/125 OM3	50/125 OM3	4	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920308	HITRONIC® HQW-Plus3000 8G 50/125 OM3	50/125 OM3	8	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920312	HITRONIC® HQW-Plus3000 12G 50/125 OM3	50/125 OM3	12	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920324	HITRONIC® HQW-Plus3000 24G 50/125 OM3	50/125 OM3	24	12.6	135
Multimode G 50 OM2						
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920204	HITRONIC® HQW-Plus3000 4G 50/125 OM2	50/125 OM2	4	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920208	HITRONIC® HQW-Plus3000 8G 50/125 OM2	50/125 OM2	8	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920212	HITRONIC® HQW-Plus3000 12G 50/125 OM2	50/125 OM2	12	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920224	HITRONIC® HQW-Plus3000 24G 50/125 OM2	50/125 OM2	24	12.6	135
Multimode G 62.5 OM1						
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920104	HITRONIC® HQW-Plus3000 4G 62.5/125 OM1	62.5/125 OM1	4	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920108	HITRONIC® HQW-Plus3000 8G 62.5/125 OM1	62.5/125 OM1	8	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920112	HITRONIC® HQW-Plus3000 12G 62.5/125 OM1	62.5/125 OM1	12	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920124	HITRONIC® HQW-Plus3000 24G 62.5/125 OM1	62.5/125 OM1	24	12.6	135
Single-mode E 9 OS2						
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920904	HITRONIC® HQW-Plus3000 4E 9/125 OS2	9/125 OS2	4	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920908	HITRONIC® HQW-Plus3000 8E 9/125 OS2	9/125 OS2	8	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920912	HITRONIC® HQW-Plus3000 12E 9/125 OS2	9/125 OS2	12	9.6	95
HITRONIC HQW-Plus Armoured Outdoor Cable	Lapp 27920924	HITRONIC® HQW-Plus3000 24E 9/125 OS2	9/125 OS2	24	12.6	135