



**Description:** HITRONIC HVN-Mini Outdoor Cable\_

**Lapp code:** Lapp 26609924

The **Test voltage** of the cable Lapp 26609924 is /.

## Application range

- For outdoor use, Backbone-Area
- For installations by blowing
- Telecommunications network
- WAN applications
- Methods of Deployment: empty plastic pipes, ducts and trays

## Product Make-up

- Up to 12 stranded gel-filled loose tubes
- Central GRP strength element
- Reinforced glass yarn strain relief
- PE outer sheath
- Colour: black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 26609924 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Fibre type	Number of fibres	Outer diameter (mm)	Weight (kg/km)
Single-mode E 9 OS2						
HITRONIC HVN-Mini Outdoor Cable	Lapp 26609912	HITRONIC® HVN-Mini500 1x12E 9/125 OS2	9/125 OS2	12	5.8	30
HITRONIC HVN-Mini Outdoor Cable	Lapp 26609924	HITRONIC® HVN-Mini500 2x12E 9/125 OS2	9/125 OS2	24	5.8	30
HITRONIC HVN-Mini Outdoor Cable	Lapp 26609948	HITRONIC® HVN-Mini500 4x12E 9/125 OS2	9/125 OS2	48	5.8	33
HITRONIC HVN-Mini Outdoor Cable	Lapp 26609972	HITRONIC® HVN-Mini500 6x12E 9/125 OS2	9/125 OS2	72	5.8	33
HITRONIC HVN-Mini Outdoor Cable	Lapp 26609996	HITRONIC® HVN-Mini1200 8x12E 9/125 OS2	9/125 OS2	96	7.2	52
HITRONIC HVN-Mini Outdoor Cable	Lapp 26609944	HITRONIC® HVN-Mini1000 12x12E 9/125	9/125 OS2	144	8.0	80