



Description: HOTY heat-shrink tube_
Lapp code: Lapp 61716740

The **Test voltage** of the cable Lapp 61716740 is Dielectric strength: 20 kV/mm.

Application range

- HOTY heat-shrink tubing is used for protecting and insulating contacts, cable lugs, connectors etc.

/

In our Cable list on next page you can find all interesting information acc. article Lapp 61716740 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article description | Internal Ø before contraction (mm) | Shrinkage range (mm) | Panel thickness/ shrunk +- 0.1 mm | PU (m) |
|-----------------------|---------------|---------------------|------------------------------------|----------------------|-----------------------------------|--------|
| HOTY heat-shrink tube | Lapp 61716700 | HOTY 1 | 2.5 | 1,2 - 2,5 | 0.45 | 100.0 |
| HOTY heat-shrink tube | Lapp 61716720 | HOTY 2 | 4 | 2 - 4 | 0.5 | 100.0 |
| HOTY heat-shrink tube | Lapp 61716740 | HOTY 3 | 6 | 3 - 6 | 0.5 | 100.0 |
| HOTY heat-shrink tube | Lapp 61716760 | HOTY 4 | 7 | 4 - 7 | 0.5 | 100.0 |
| HOTY heat-shrink tube | Lapp 61716780 | HOTY 6 | 11 | 6 - 11 | 0.6 | 100.0 |
| HOTY heat-shrink tube | Lapp 61716800 | HOTY 8 | 14 | 8 - 14 | 0.6 | 100.0 |
| HOTY heat-shrink tube | Lapp 61716820 | HOTY 10 | 17 | 10 - 17 | 0.8 | 100.0 |
| HOTY heat-shrink tube | Lapp 61716840 | HOTY 13 | 20 | 13 - 20 | 1 | 100.0 |
| HOTY heat-shrink tube | Lapp 61716860 | HOTY 16 | 25 | 16 - 25 | 1 | 50.0 |
| HOTY heat-shrink tube | Lapp 61716880 | HOTY 20 | 31 | 20 - 31 | 1 | 50.0 |