



Description: J-H(ST)H...BD 2 x 2 x 0,6_

Lapp code: Lapp 3022220

The **Test voltage** of the cable Lapp 3022220 is Core/core: 800 V Core/screen: 800 V.

Application range

- This halogen-free, flame-retardant installation cable with static screen is used for telephone, data and signal transmission in subscriber stations and private branch exchange construction for telephone systems
- For fixed installation on and under plaster, in dry and damp rooms

Product Make-up

- Solid bare copper conductor
- Core insulation made of special halogen-free compound
- Cores twisted into star quads,
5 star quads are twisted into a bundle,
bundles stranded in layers
- Foil wrapping,
static screening made of aluminium-laminated plastic film with copper drain wire
- Outer sheath made of special halogen-free compound
Outer sheath colour: grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 3022220 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of pairs and conductor diameter (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
J-H(ST)H-BD					
J-H(ST)H...BD 2 x 2 x 0,6	Lapp 3022220	2 x 2 x 0,6	5.5	14.1	65
J-H(ST)H...BD 4 x 2 x 0,6	Lapp 3022221	4 x 2 x 0,6	7.5	25.4	100
J-H(ST)H...BD 6 x 2 x 0,6	Lapp 3022222	6 x 2 x 0,6	7.8	37.0	117
J-H(ST)H...BD 10 x 2 x 0,6	Lapp 3022223	10 x 2 x 0,6	9.2	59.0	155
J-H(ST)H...BD 2 x 2 x 0,8	Lapp 30017787	2 x 2 x 0,8	7.0	25.0	77
J-H(ST)H...BD 4 x 2 x 0,8	Lapp 30017788	4 x 2 x 0,8	9.2	45.0	135