



Description: J-Y(ST)Y...LG Fire Alarm Cable 10 x 2 x 0,8_

Lapp code: Lapp 1708010

The **Test voltage** of the cable Lapp 1708010 is Core/core: 800 V Core/screen: 800 V.

Application range

- This installation cable is used to transmit signals.
- For fixed installation on and under plaster, in dry and damp rooms
- For outdoor use this cable should be installed under plaster only

Product Make-up

- Solid bare copper conductor
- Core insulation made of PVC
- Cores twisted in pairs,
pairs twisted together,
foil wrapping over cable core,
static screen made of aluminium-laminated plastic film with copper drain wire
- Outer sheath made of PVC
Outer sheath colour: flame red (RAL 3000)

In our Cable list on next page you can find all interesting information acc. article Lapp 1708010 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of pairs and conductor diameter (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
J-Y(ST)Y...LG Fire Alarm Cable					
J-Y(ST)Y...LG Fire Alarm Cable 1 x 2 x 0,8	Lapp 1708001	1 x 2 x 0,8	6.0	11.0	40
J-Y(ST)Y...LG Fire Alarm Cable 2 x 2 x 0,8	Lapp 1708002	2 x 2 x 0,8	7.0	21.0	60
J-Y(ST)Y...LG Fire Alarm Cable 4 x 2 x 0,8	Lapp 1708004	4 x 2 x 0,8	9.0	41.0	100
J-Y(ST)Y...LG Fire Alarm Cable 6 x 2 x 0,8	Lapp 1708006	6 x 2 x 0,8	10.5	62.0	140
J-Y(ST)Y...LG Fire Alarm Cable 10 x 2 x 0,8	Lapp 1708010	10 x 2 x 0,8	13.5	102.0	220
J-Y(ST)Y...LG Fire Alarm Cable 20 x 2 x 0,8	Lapp 1708020	20 x 2 x 0,8	16.5	204.0	380