



Description: JE-LiYCY...BD 24 x 2 x 0,5_

Lapp code: Lapp 0034204

The **Test voltage** of the cable Lapp 0034204 is Core/core: 500 V Core/screen: 2000 V.

Application range

- Connection cable for use in electronics and in measurement, control and signal applications
- This cable is also used as a pulse and data transmission cable
- JE-LiYCY...BD has also proved to be an efficient connection cable for telephone systems, e.g. paging and intercom systems.
- For fixed installation on and under plaster, in dry and damp rooms
- For outdoor use this cable should be installed under plaster only

Product Make-up

- 7-wire bare stranded copper conductor
- Core insulation made of PVC
- 2 cores twisted into a pair, and 4 pairs into units (for 2 x 2 x 0.5 as star quad cable)
- Bundles twisted in layers,
foil wrapping,
screening braid made of tinned copper wires
- Outer sheath made of PVC
Outer sheath colour: pebble grey (RAL 7032)

In our Cable list on next page you can find all interesting information acc. article Lapp 0034204 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of pairs and conductor cross section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
JE-LiYCY...BD					
JE-LiYCY...BD 2 x 2 x 0,5	Lapp 0034200	2 x 2 x 0,5	7.5	51.0	70
JE-LiYCY...BD 4 x 2 x 0,5	Lapp 0034201	4 x 2 x 0,5	10.0	87.0	155
JE-LiYCY...BD 8 x 2 x 0,5	Lapp 0034202	8 x 2 x 0,5	13.0	144.0	260
JE-LiYCY...BD 12 x 2 x 0,5	Lapp 0034208	12 x 2 x 0,5	15.5	195.0	340
JE-LiYCY...BD 16 x 2 x 0,5	Lapp 0034203	16 x 2 x 0,5	17.0	249.0	430
JE-LiYCY...BD 20 x 2 x 0,5	Lapp 0034210	20 x 2 x 0,5	18.5	298.0	495
JE-LiYCY...BD 24 x 2 x 0,5	Lapp 0034204	24 x 2 x 0,5	20.5	348.0	605
JE-LiYCY...BD 32 x 2 x 0,5	Lapp 0034212	32 x 2 x 0,5	22.5	441.0	738