



**Description:** JE-Y(ST)Y...BD 40 x 2 x 0,8\_

**Lapp code:** Lapp 0034197

The **Test voltage** of the cable Lapp 0034197 is Core/core: 500 V Core/screen: 2000 V.

## Application range

- Connection cable for fixed installation in industrial control systems, as required in measurement, control, signalling and data applications
- Industrial electronics
- For fixed installation on and under plaster, in dry and damp rooms
- For outdoor use this cable should be installed under plaster only

## Product Make-up

- Solid bare copper conductor
- Core insulation made of PVC
- 2 cores twisted into a pair, and 4 pairs into units (for 2 x 2 x 0.8 as star quad cable)
- Foil wrapping,  
static screening made of aluminium-laminated plastic film with copper drain wire
- Outer sheath made of PVC  
Outer sheath colour: pebble grey (RAL 7032)

In our Cable list on next page you can find all interesting information acc. article Lapp 0034197 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and cable diameter (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
JE-Y(ST)Y...BD					
JE-Y(ST)Y...BD 2 x 2 x 0,8	Lapp 0034190	2 x 2 x 0,8	6.0	25.0	60
JE-Y(ST)Y...BD 4 x 2 x 0,8	Lapp 0034191	4 x 2 x 0,8	8.5	45.0	96
JE-Y(ST)Y...BD 8 x 2 x 0,8	Lapp 0034192	8 x 2 x 0,8	11.0	85.0	158
JE-Y(ST)Y...BD 12 x 2 x 0,8	Lapp 0034193	12 x 2 x 0,8	13.0	126.0	225
JE-Y(ST)Y...BD 16 x 2 x 0,8	Lapp 0034194	16 x 2 x 0,8	14.5	166.0	290
JE-Y(ST)Y...BD 20 x 2 x 0,8	Lapp 0034195	20 x 2 x 0,8	16.0	206.0	350
JE-Y(ST)Y...BD 40 x 2 x 0,8	Lapp 0034197	40 x 2 x 0,8	22.0	407.0	660