



Description: JE-Y(ST)Y...BD EB 20 x 2 x 0,8_

Lapp code: Lapp 0034125

The **Test voltage** of the cable Lapp 0034125 is Core/core: 500 V Core/screen: 2000 V.

Application range

- Connection cable for fixed installation in industrial control systems, as required in measurement, control, signalling and data applications
- Industrial electronics
- For fixed installation on and under plaster, in dry and damp rooms
- For outdoor use this cable should be installed under plaster only

Product Make-up

- Solid bare copper conductor
- Core insulation made of PVC
- 2 cores twisted into a pair, and 4 pairs into units (for 2 x 2 x 0.8 as star quad cable)
- Foil wrapping,
static screening made of aluminium-laminated plastic film with copper drain wire
- Outer sheath made of PVC
Outer sheath colour: sky blue (RAL 5015)

In our Cable list on next page you can find all interesting information acc. article Lapp 0034125 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and cable diameter (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
JE-Y(ST)Y...BD EB, blue outer sheath					
JE-Y(ST)Y...BD EB 2 x 2 x 0,8	Lapp 0034120	2 x 2 x 0,8	6.0	25.0	60
JE-Y(ST)Y...BD EB 4 x 2 x 0,8	Lapp 0034121	4 x 2 x 0,8	8.5	45.0	100
JE-Y(ST)Y...BD EB 8 x 2 x 0,8	Lapp 0034122	8 x 2 x 0,8	11.0	85.0	165
JE-Y(ST)Y...BD EB 12 x 2 x 0,8	Lapp 0034123	12 x 2 x 0,8	13.0	126.0	240
JE-Y(ST)Y...BD EB 20 x 2 x 0,8	Lapp 0034125	20 x 2 x 0,8	16.0	206.0	360
JE-Y(ST)Y...BD EB 32 x 2 x 0,8	Lapp 0034126	32 x 2 x 0,8	20.0	327.0	555