



Description: JE-Y(ST)Y...BD EB 8 x 2 x 0,8_

Lapp code: Lapp 0034122

The **Test voltage** of the cable Lapp 0034122 is Core/core: 500 V Core/screen: 2000 V.

Application range

- Connection cable for fixed installation in industrial control systems, as required in measurement, control, signalling and data applications
- Industrial electronics
- For fixed installation on and under plaster, in dry and damp rooms
- For outdoor use this cable should be installed under plaster only

Product Make-up

- Solid bare copper conductor
- Core insulation made of PVC
- 2 cores twisted into a pair, and 4 pairs into units (for 2 x 2 x 0.8 as star quad cable)
- Foil wrapping,
static screening made of aluminium-laminated plastic film with copper drain wire
- Outer sheath made of PVC
Outer sheath colour: sky blue (RAL 5015)

In our Cable list on next page you can find all interesting information acc. article Lapp 0034122 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and cable diameter (mm) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------------|--------------|---|---------------------|----------------------|----------------|
| JE-Y(ST)Y...BD EB, blue outer sheath | | | | | |
| JE-Y(ST)Y...BD EB 2 x 2 x 0,8 | Lapp 0034120 | 2 x 2 x 0,8 | 6.0 | 25.0 | 60 |
| JE-Y(ST)Y...BD EB 4 x 2 x 0,8 | Lapp 0034121 | 4 x 2 x 0,8 | 8.5 | 45.0 | 100 |
| JE-Y(ST)Y...BD EB 8 x 2 x 0,8 | Lapp 0034122 | 8 x 2 x 0,8 | 11.0 | 85.0 | 165 |
| JE-Y(ST)Y...BD EB 12 x 2 x 0,8 | Lapp 0034123 | 12 x 2 x 0,8 | 13.0 | 126.0 | 240 |
| JE-Y(ST)Y...BD EB 20 x 2 x 0,8 | Lapp 0034125 | 20 x 2 x 0,8 | 16.0 | 206.0 | 360 |
| JE-Y(ST)Y...BD EB 32 x 2 x 0,8 | Lapp 0034126 | 32 x 2 x 0,8 | 20.0 | 327.0 | 555 |