



Description: Li2YCY 0,25_
Lapp code: Lapp 4550116

The **Test voltage** of the cable Lapp 4550116 is 1200 V.

Application range

- Wiring of measuring instruments, switch cabinets, electrical components, transmitters and receivers
- In EMC-sensitive environments

Product Make-up

- Strands of tinned-copper wires
- Core insulation: PE
- Wrapped screening made from tinned copper wire
- PVC-based outer sheath, transparent

In our Cable list on next page you can find all interesting information acc. article Lapp 4550116 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm ²)	Number of wires x wire-Ø (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Li2YCY 0,14	Lapp 4550115	0,14	18 x 0,1	2.3	7.0	10
Li2YCY 0,25	Lapp 4550116	0,25	14 x 0,15	2.5	9.0	15
Li2YCY 0,5	Lapp 4550117	0,5	16 x 0,2	3.1	15.0	19.5
Li2YCY 0,75	Lapp 4550118	0,75	24 x 0,2	3.3	18.0	28
Li2YCY 1	Lapp 4550119	1	32 x 0,2	3.7	25.0	30