



Description: LiFY 0,75_

Lapp code: Lapp 4560017S

The **Test voltage** of the cable Lapp 4560017S is /.

Application range

- For use in and on mobile equipment
- For measuring assemblies in technical training sessions, education and electric laboratories

Product Make-up

- Stranded copper wire
- Core insulation: Based on PVC

In our Cable list on next page you can find all interesting information acc. article Lapp 4560017S and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm ²)	Outer diameter (mm)	Core colour	Copper index (kg/km)	PU
LiFY 0,75	Lapp 4560017S	0,75	2,5	green/yellow	7.2	100
LiFY 0,75	Lapp 4560013S	0,75	2,5	black	7.2	100
LiFY 0,75	Lapp 4560014S	0,75	2,5	blue	7.2	100
LiFY 0,75	Lapp 4560016S	0,75	2,5	red	7.2	100
LiFY 1	Lapp 4560027S	1	2,9	green/yellow	9.6	100
LiFY 1	Lapp 4560023S	1	2,9	black	9.6	100
LiFY 1	Lapp 4560024S	1	2,9	blue	9.6	100
LiFY 1	Lapp 4560026S	1	2,9	red	9.6	100
LiFY 1,5	Lapp 4560037S	1,5	3,7	green/yellow	14.4	100
LiFY 1,5	Lapp 4560033S	1,5	3,7	black	14.4	100
LiFY 1,5	Lapp 4560034S	1,5	3,7	blue	14.4	100
LiFY 1,5	Lapp 4560036S	1,5	3,7	red	14.4	100
LiFY 2,5	Lapp 4560057S	2,5	4,2	green/yellow	24.0	50
LiFY 2,5	Lapp 4560053S	2,5	4,2	black	24.0	50
LiFY 2,5	Lapp 4560054S	2,5	4,2	blue	24.0	50
LiFY 2,5	Lapp 4560056S	2,5	4,2	red	24.0	50
LiFY 4	Lapp 4560063	4	5,1	black	38.4	100
LiFY 4	Lapp 4560067	4	5,1	green/yellow	38.4	100
LiFY 4	Lapp 4560064	4	5,1	blue	38.4	100
LiFY 6	Lapp 4560077	6	6.0	green/yellow	57.6	50
LiFY 6	Lapp 4560073	6	6.0	black	57.6	50
LiFY 6	Lapp 4560074	6	6.0	blue	57.6	50
LiFY 6	Lapp 4560076	6	6.0	red	57.6	50
LiFY 10	Lapp 4560087	10	7,4	green/yellow	96.0	50
LiFY 10	Lapp 4560083	10	7,4	black	107.5	50
LiFY 10	Lapp 4560086	10	7,4	red	96.0	50