



Description: LiY 0,25_

Lapp code: Lapp 4126005S

The **Test voltage** of the cable Lapp 4126005S is 1200 V (0.14 mm²) 2500 V (0.25 mm²).

Application range

- Stranded hook-up wires for wiring of telecommunication devices and electronic components within devices

Product Make-up

- Stranded copper wire
- Core insulation: PVC-based YI 2/TI 2 acc. VDE 0207-4

In our Cable list on next page you can find all interesting information acc. article Lapp 4126005S and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm ²)	Outer diameter (mm)	Core colour	m/spool	Copper index (kg/km)
LiY 0,14	Lapp 4125001S	0,14	1.1	black	500	1.35
LiY 0,14	Lapp 4125002S	0,14	1.1	blue	500	1.35
LiY 0,14	Lapp 4125003S	0,14	1.1	brown	500	1.35
LiY 0,14	Lapp 4125005S	0,14	1.1	yellow	500	1.35
LiY 0,14	Lapp 4125006S	0,14	1.1	green	500	1.35
LiY 0,14	Lapp 4125007S	0,14	1.1	violet	500	1.35
LiY 0,14	Lapp 4125009S	0,14	1.1	orange	500	1.35
LiY 0,14	Lapp 4125104S	0,14	1.1	red	500	1.35
LiY 0,14	Lapp 4125105S	0,14	1.1	white	500	1.35
LiY 0,14	Lapp 4125106S	0,14	1.1	grey	500	1.35
LiY 0,25	Lapp 4126000S	0,25	1.3	green/yellow	250	2.4
LiY 0,25	Lapp 4126001S	0,25	1.3	black	250	2.4
LiY 0,25	Lapp 4126002S	0,25	1.3	blue	250	2.4
LiY 0,25	Lapp 4126014S	0,25	1.3	Dark blue	250	2.4
LiY 0,25	Lapp 4126003S	0,25	1.3	brown	250	2.4
LiY 0,25	Lapp 4126005S	0,25	1.3	yellow	250	2.4
LiY 0,25	Lapp 4126006S	0,25	1.3	green	250	2.4
LiY 0,25	Lapp 4126007S	0,25	1.3	violet	250	2.4
LiY 0,25	Lapp 4126008S	0,25	1.3	pink	250	2.4
LiY 0,25	Lapp 4126009S	0,25	1.3	orange	250	2.4
LiY 0,25	Lapp 4126104S	0,25	1.3	red	250	2.4
LiY 0,25	Lapp 4126105S	0,25	1.3	white	250	2.4
LiY 0,25	Lapp 4126106S	0,25	1.3	grey	250	2.4