



Description: LiYCY 0,25_
Lapp code: Lapp 4530102

The **Test voltage** of the cable Lapp 4530102 is 800 V.

Application range

- Wiring of measuring instruments, switch cabinets, electrical components, transmitters and receivers
- In EMC-sensitive environments

Product Make-up

- Strands of tinned-copper wires
- Core insulation: Based on PVC
- Tinned-copper braiding
- PVC-based outer sheath, transparent

In our Cable list on next page you can find all interesting information acc. article Lapp 4530102 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Conductor cross-section (mm ²)	Number of wires x wire-Ø (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
LiYCY 0,14	Lapp 4530101	0,14	18 x 0,1	2.8	7.0	13
LiYCY 0,25	Lapp 4530102	0,25	14 x 0,15	3.3	9.0	18
LiYCY 0,5	Lapp 4530103	0,5	16 x 0,2	3.6	15.0	20
LiYCY 0,75	Lapp 4530104	0,75	24 x 0,2	3.9	18.0	31
LiYCY 1	Lapp 4530105	1	32 x 0,2	4.7	25.0	35.9
LiYCY 1,5	Lapp 4530106	1,5	30 x 0,25	4.7	30.0	39
LiYCY 2,5	Lapp 4530107	2,5	50 x 0,25	6.0	35.0	55.3