



Description: (N)HXMH 5 G 2,5_
Lapp code: Lapp 16020123

The **Test voltage** of the cable Lapp 16020123 is 2000 V.

Application range

- For installation on or under the plaster
- In bricks and concrete, except direct embedding in vibrated or compressed concrete
- In dry, damp or wet interiors
- For buildings or industrial plants with a high density of people or valuable assets

Product Make-up

- Bare copper wire conductor
- Core insulation: PE
- Filling compound over the core assembly
- Outer sheath: halogen-free polymer

In our Cable list on next page you can find all interesting information acc. article Lapp 16020123 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
(N)HXMH 3 G 1,5	Lapp 16020003	3 G 1,5	8,5	43.0	120
(N)HXMH 4 G 1,5	Lapp 16020013	4 G 1,5	9,3	58.0	145
(N)HXMH 5 G 1,5	Lapp 16020023	5 G 1,5	10.0	72.0	170
(N)HXMH 7 G 1,5	Lapp 1602003	7 G 1,5	10,8	101.0	210
(N)HXMH 3 G 2,5	Lapp 16020103	3 G 2,5	9,4	72.0	160
(N)HXMH 5 G 2,5	Lapp 16020123	5 G 2,5	11.0	120.0	230