



**Description:** NSSHÖU 1 X 150\_  
**Lapp code:** Lapp 1600507

The **Test voltage** of the cable Lapp 1600507 is 3000 V.

## Application range

- For mining as well as surface mining
- Connection for moving equipment and machinery
- Under extreme environmental conditions
- Suitable for outdoor use, as well as in dry and damp interiors

## Product Make-up

- Fine-wire strand made of tinned-copper wires
- Core insulation: rubber compound type 3GI3
- Inner sheath: rubber-compound, type GM1b or 5GM5
- Outer sheath: rubber compound, type 5GM5

In our Cable list on next page you can find all interesting information acc. article Lapp 1600507 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
NSSHÖU-O					
NSSHÖU 1 X 16	Lapp 1600500	1 X 16	10,9	153.6	260
NSSHÖU 1 X 25	Lapp 1600501	1 X 25	13,3	240.0	390
NSSHÖU 1 X 35	Lapp 1600502	1 X 35	14,4	336.0	500
NSSHÖU 1 X 50	Lapp 1600503	1 X 50	16,7	480.0	680
NSSHÖU 1 X 70	Lapp 1600504	1 X 70	18,9	672.0	900
NSSHÖU 1 X 95	Lapp 1600505	1 X 95	21.0	912.0	1150
NSSHÖU 1 X 120	Lapp 1600506	1 X 120	23,3	1152.0	1440
NSSHÖU 1 X 150	Lapp 1600507	1 X 150	25,2	1440.0	1750
NSSHÖU 1 X 185	Lapp 1600508	1 X 185	28,4	1776.0	2180
NSSHÖU 1 X 240	Lapp 1600509	1 X 240	31,4	2304.0	2790
NSSHÖU-J					
NSSHÖU 3 G 1,5	Lapp 1600516	3 G 1,5	11,8	43.2	200
NSSHÖU 4 G 1,5	Lapp 16005243	4 G 1,5	12,7	57.6	230
NSSHÖU 5 G 1,5	Lapp 16005333	5 G 1,5	13,6	72.0	280
NSSHÖU 3 G 2,5	Lapp 1600517	3 G 2,5	13,2	72.0	260
NSSHÖU 4 G 2,5	Lapp 16005253	4 G 2,5	15,4	96.0	360
NSSHÖU 5 G 2,5	Lapp 16005343	5 G 2,5	16,5	120.0	420
NSSHÖU 7 G 2,5	Lapp 1600541	7 G 2,5	20.0	168.0	600
NSSHÖU 12 G 2,5	Lapp 1600544	12 G 2,5	26.0	288.0	860
NSSHÖU 4 G 4	Lapp 16005263	4 G 4	16,9	153.6	470
NSSHÖU 5 G 4	Lapp 16005353	5 G 4	18,2	192.0	550
NSSHÖU 4 G 6	Lapp 16005273	4 G 6	18,3	230.4	580
NSSHÖU 5 G 6	Lapp 16005363	5 G 6	20,6	288.0	740
NSSHÖU 4 G 10	Lapp 16005283	4 G 10	22,3	384.0	950
NSSHÖU 5 G 10	Lapp 16005373	5 G 10	24,1	480.0	1100
NSSHÖU 4 G 16	Lapp 16005293	4 G 16	26,1	614.0	1400
NSSHÖU 5 G 16	Lapp 16005383	5 G 16	28,3	768.0	1720
NSSHÖU 4 G 25	Lapp 16005303	4 G 25	31,2	960.0	2000
NSSHÖU 4 G 35	Lapp 16005313	4 G 35	34,1	1344.0	2700
NSSHÖU 4 G 50	Lapp 16005323	4 G 50	41.0	1920.0	3700