



Description: NSSHÖU 7 G 2,5_
Lapp code: Lapp 1600541

The **Test voltage** of the cable Lapp 1600541 is 3000 V.

Application range

- For mining as well as surface mining
- Connection for moving equipment and machinery
- Under extreme environmental conditions
- Suitable for outdoor use, as well as in dry and damp interiors

Product Make-up

- Fine-wire strand made of tinned-copper wires
- Core insulation: rubber compound type 3GI3
- Inner sheath: rubber-compound, type GM1b or 5GM5
- Outer sheath: rubber compound, type 5GM5

In our Cable list on next page you can find all interesting information acc. article Lapp 1600541 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------|---------------|---------------------------------------------------|---------------------|----------------------|----------------|
| NSSHÖU-O | | | | | |
| NSSHÖU 1 X 16 | Lapp 1600500 | 1 X 16 | 10,9 | 153.6 | 260 |
| NSSHÖU 1 X 25 | Lapp 1600501 | 1 X 25 | 13,3 | 240.0 | 390 |
| NSSHÖU 1 X 35 | Lapp 1600502 | 1 X 35 | 14,4 | 336.0 | 500 |
| NSSHÖU 1 X 50 | Lapp 1600503 | 1 X 50 | 16,7 | 480.0 | 680 |
| NSSHÖU 1 X 70 | Lapp 1600504 | 1 X 70 | 18,9 | 672.0 | 900 |
| NSSHÖU 1 X 95 | Lapp 1600505 | 1 X 95 | 21.0 | 912.0 | 1150 |
| NSSHÖU 1 X 120 | Lapp 1600506 | 1 X 120 | 23,3 | 1152.0 | 1440 |
| NSSHÖU 1 X 150 | Lapp 1600507 | 1 X 150 | 25,2 | 1440.0 | 1750 |
| NSSHÖU 1 X 185 | Lapp 1600508 | 1 X 185 | 28,4 | 1776.0 | 2180 |
| NSSHÖU 1 X 240 | Lapp 1600509 | 1 X 240 | 31,4 | 2304.0 | 2790 |
| NSSHÖU-J | | | | | |
| NSSHÖU 3 G 1,5 | Lapp 1600516 | 3 G 1,5 | 11,8 | 43.2 | 200 |
| NSSHÖU 4 G 1,5 | Lapp 16005243 | 4 G 1,5 | 12,7 | 57.6 | 230 |
| NSSHÖU 5 G 1,5 | Lapp 16005333 | 5 G 1,5 | 13,6 | 72.0 | 280 |
| NSSHÖU 3 G 2,5 | Lapp 1600517 | 3 G 2,5 | 13,2 | 72.0 | 260 |
| NSSHÖU 4 G 2,5 | Lapp 16005253 | 4 G 2,5 | 15,4 | 96.0 | 360 |
| NSSHÖU 5 G 2,5 | Lapp 16005343 | 5 G 2,5 | 16,5 | 120.0 | 420 |
| NSSHÖU 7 G 2,5 | Lapp 1600541 | 7 G 2,5 | 20.0 | 168.0 | 600 |
| NSSHÖU 12 G 2,5 | Lapp 1600544 | 12 G 2,5 | 26.0 | 288.0 | 860 |
| NSSHÖU 4 G 4 | Lapp 16005263 | 4 G 4 | 16,9 | 153.6 | 470 |
| NSSHÖU 5 G 4 | Lapp 16005353 | 5 G 4 | 18,2 | 192.0 | 550 |
| NSSHÖU 4 G 6 | Lapp 16005273 | 4 G 6 | 18,3 | 230.4 | 580 |
| NSSHÖU 5 G 6 | Lapp 16005363 | 5 G 6 | 20,6 | 288.0 | 740 |
| NSSHÖU 4 G 10 | Lapp 16005283 | 4 G 10 | 22,3 | 384.0 | 950 |
| NSSHÖU 5 G 10 | Lapp 16005373 | 5 G 10 | 24,1 | 480.0 | 1100 |
| NSSHÖU 4 G 16 | Lapp 16005293 | 4 G 16 | 26,1 | 614.0 | 1400 |
| NSSHÖU 5 G 16 | Lapp 16005383 | 5 G 16 | 28,3 | 768.0 | 1720 |
| NSSHÖU 4 G 25 | Lapp 16005303 | 4 G 25 | 31,2 | 960.0 | 2000 |
| NSSHÖU 4 G 35 | Lapp 16005313 | 4 G 35 | 34,1 | 1344.0 | 2700 |
| NSSHÖU 4 G 50 | Lapp 16005323 | 4 G 50 | 41.0 | 1920.0 | 3700 |