



Description: NYM-J 1 G 16_
Lapp code: Lapp 1600012

The **Test voltage** of the cable Lapp 1600012 is 2000 V.

Application range

- For installation on or under the plaster
- In bricks and concrete, except direct embedding in vibrated or compressed concrete
- In dry, damp or wet interiors
- Also suitable for outdoor use if protected against direct sunlight

Product Make-up

- Bare copper wire conductor
- Core insulation: Based on PVC
- Filling compound over the core assembly
- PVC-based outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 1600012 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
NYM-J 1 G 2,5	Lapp 1600008	1 G 2,5	6,0	24,0	60
NYM-J 1 G 4	Lapp 1600009	1 G 4	6,7	38,0	85
NYM-J 1 G 6	Lapp 1600010	1 G 6	7,2	58,0	105
NYM-J 1 G 10	Lapp 1600011	1 G 10	8,6	96,0	160
NYM-J 1 G 16	Lapp 1600012	1 G 16	9,6	154,0	220
NYM-J 3 G 1,5	Lapp 16000003	3 G 1,5	8,4	43,0	120
NYM-J 4 G 1,5	Lapp 16000013	4 G 1,5	9,2	58,0	150
NYM-J 5 G 1,5	Lapp 16000023	5 G 1,5	9,9	72,0	175
NYM-J 7 G 1,5	Lapp 1600003	7 G 1,5	11,6	101,0	235
NYM-J 3 G 2,5	Lapp 16000213	3 G 2,5	9,6	72,0	170
NYM-J 4 G 2,5	Lapp 16000053	4 G 2,5	10,6	96,0	210
NYM-J 5 G 2,5	Lapp 16000063	5 G 2,5	11,5	120,0	290
NYM-J 7 G 2,5	Lapp 1600071	7 G 2,5	13,7	168,0	380
NYM-J 3 G 4	Lapp 16010223	3 G 4	11,3	115,0	250
NYM-J 4 G 4	Lapp 16000313	4 G 4	12,7	154,0	315
NYM-J 5 G 4	Lapp 16000513	5 G 4	14,0	192,0	370
NYM-J 3 G 6	Lapp 16010233	3 G 6	12,8	173,0	335
NYM-J 4 G 6	Lapp 16000323	4 G 6	13,8	230,0	410
NYM-J 5 G 6	Lapp 16000523	5 G 6	15,5	288,0	500
NYM-J 4 G 10	Lapp 16000333	4 G 10	18,0	384,0	680
NYM-J 5 G 10	Lapp 16000533	5 G 10	19,5	480,0	810
NYM-J 5 G 16	Lapp 16000543	5 G 16	23,0	768,0	1200
NYM-J 4 G 25	Lapp 16000353	4 G 25	26,0	960,0	1500
NYM-J 5 G 25	Lapp 16000553	5 G 25	28,0	1200,0	1800