



Description: Panel connectors insulated_

Lapp code: Lapp 61794971

The **Test voltage** of the cable Lapp 61794971 is /.

Application range

- For breaking through the oxidation layer on the conductor when crimping

/

In our Cable list on next page you can find all interesting information acc. article Lapp 61794971 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	For mm ²	UL approval	Footnote	Colour	Blade connection	d mm	L	W mm	Pieces / PU
Blade receptacle according to DIN 46245 and similar (type H)											
Panel connectors insulated	Lapp 63101020	L-RA 29 H	0,5 - 1,5	yes		red	2.8 x 0.5	3.3	18.5	3.5	100
Panel connectors insulated	Lapp 63101010	L-RA 28 H	0,5 - 1,5	yes		red	2.8 x 0.8	3.3	18.5	3.5	100
Panel connectors insulated	Lapp 63101030	L-RA 49 H	0,5 - 1,5	yes	1.3	red	4.8 x 0.5	3.7	19.0	5.7	100
Panel connectors insulated	Lapp 63101040	L-RA 48 H	0,5 - 1,5	yes	1.3	red	4.8 x 0.8	3.7	19.0	5.7	100
Panel connectors insulated	Lapp 63101050	L-RA 63 H	0,5 - 1,5	yes		red	6.3 x 0.8	4.0	20.0	7.6	100
Panel connectors insulated	Lapp 63101060	L-RB 48 H	1,5 - 2,5	yes	1.3	blue	4.8 x 0.5	4.4	19.0	5.7	100
Panel connectors insulated	Lapp 63101070	L-RB 49 H	1,5 - 2,5	yes	1.3	blue	4.8 x 0.8	4.4	19.0	5.7	100
Panel connectors insulated	Lapp 63101080	L-RB 63 H	1,5 - 2,5	yes		blue	6.3 x 0.8	4.5	20.0	7.6	100
Panel connectors insulated	Lapp 63101110	L-RC 63 H	4 - 6	yes		yellow	6.3 x 0.8	6.4	24.0	7.6	100
Panel connectors insulated	Lapp 63101120	L-RC 95 H	4 - 6	no		yellow	9.5 x 1.2	6.2	31.0	11.0	100
Blade connector (type M)											
Panel connectors insulated	Lapp 63103010	L-RA 63 M	0,5 - 1,5	yes		red	6.3 x 0.8	4.0	22.0		100
Panel connectors insulated	Lapp 63103020	L-RB 63 M	1,5 - 2,5	yes		blue	6.3 x 0.8	4.5	22.0		100
Panel connectors insulated	Lapp 63103040	L-RC 63 M	4 - 6	yes	1.3	yellow	6.3 x 0.8	6.3	25.0		100
Blade receptacle branch (type T)											
Panel connectors insulated	Lapp 63102010	L-RA 63 T	0,5 - 1,5	no	1.3	red	6.3 x 0.8	3.7	22.0	7.4	100
Panel connectors insulated	Lapp 63102020	L-RB 63 T	1,5 - 2,5	no	1.3	blue	6.3 x 0.8	4.3	22.0	7.5	50
Fully insulated blade receptacle (type V)											
Panel connectors insulated	Lapp 61794951	L-RA 29 V	0,5 - 1,5	yes	2.3	red	2.8 x 0.5	3.8	19.3	5.0	100

Panel connectors insulated_

Lapp 61794971



Product Name	Lapp Nr.	Article designation	For mm ²	UL approval	Footnote	Colour	Blade connection	d mm	L	W mm	Pieces / PU
Panel connectors insulated	Lapp 61794952	L-RA 28 V	0,5 - 1,5	yes	2.3	red	2.8 x 0.8	3.8	19.3	5.0	100
Panel connectors insulated	Lapp 61794953	L-RA 49 V	0,5 - 1,5	yes	2.3	red	4.8 x 0.5	3.6	20.2	7.4	100
Panel connectors insulated	Lapp 61794955	L-RA 48 V	0,5 - 1,5	yes	2.3	red	4.8 x 0.8	3.6	20.2	7.4	100
Panel connectors insulated	Lapp 61794960	L-RA 63 V	0,5 - 1,5	yes		red	6.3 x 0.8	4.4	21.0	8.8	100
Panel connectors insulated	Lapp 61794968	L-RB 49 V	1,5 - 2,5	yes	2.3	blue	4.8 x 0.5	3.9	19.5	7.1	100
Panel connectors insulated	Lapp 61794969	L-RB 48 V	1,5 - 2,5	yes	2.3	blue	4.8 x 0.8	4.3	20.0	7.4	100
Panel connectors insulated	Lapp 61794970	L-RB 63 V	1,5 - 2,5	yes		blue	6.3 x 0.8	4.5	21.0	8.8	100
Panel connectors insulated	Lapp 61794971	L-RC 63 V	4 - 6	yes	2.3	yellow	6.3 x 0.8	5.3	26.0	9.0	100