



**Description:** SERVO Cables in acc. to SEW Standard 4 G 2,5 + (3 x 1,0)\_

**Lapp code:** Lapp 0038061

The **Test voltage** of the cable Lapp 0038061 is 2000 V.

## Application range

- Specially designed to connect SEW servomotors
- Connecting cable between servo controller and motor
- Plant engineering
- Machine tools
- Printing machines

## Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation: TPE
- Control core triplet with laminated aluminium film and a layer of tinned-copper wires
- Cores twisted in short lay lengths
- Tinned-copper braiding
- PVC outer sheath, orange (RAL 2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 0038061 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Servo cables					
SERVO Cables in acc. to SEW Standard 4 G 1,5 + (3 x 1,0)	Lapp 0038060	4 G 1,5 + (3 x 1,0)	11,8	151.0	300
SERVO Cables in acc. to SEW Standard 4 G 2,5 + (3 x 1,0)	Lapp 0038061	4 G 2,5 + (3 x 1,0)	13,4	212.9	370
SERVO Cables in acc. to SEW Standard 4 G 4 + (3 x 1,0)	Lapp 0038062	4 G 4 + (3 x 1,0)	15.0	281.8	476
SERVO Cables in acc. to SEW Standard 4 G 6 + (3 x 1,5)	Lapp 0038063	4 G 6 + (3 x 1,5)	17.0	392.8	625
SERVO Cables in acc. to SEW Standard 4 G 10 + (3 x 1,5)	Lapp 0038064	4 G 10 + (3 x 1,5)	20.0	625.1	1024