



Description: SILVYN AFW-PA_
Lapp code: Lapp 55001093

The **Test voltage** of the cable Lapp 55001093 is /.

Application range

- In combination with protective conduit
- SILVYN® MAXI PA
- Mechanical engineering
- Bundling and guiding of cables and wires
- For applications with limited space

Product Make-up

- One-piece 90° elbow connector with flap mechanism specifically designed for use with the SILVYN® MAXI PA. Thanks to the special design, the conduit can be pre-locked and mounted ready for connection

In our Cable list on next page you can find all interesting information acc. article Lapp 55001093 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	A [mm]	B in mm	Overall length/ C (mm)	D (mm)	E mm	F mm	H	I	J	K	L	N	O	Pieces / PU
SILVYN® AFW-PA grey																
SILVYN AF W-PA	Lapp 5 50010 90	70 - 90°- angle	94.0	96.0	60.5	80.5	96.4	69	70.0	56.5	6.2	152.5	103.5	81.5	175.0	1.0
SILVYN AF W-PA	Lapp 5 50010 91	95 - 90°- angle	128.0	126.0	74.0	108.0	123.5	96	95.0	55.0	7.0	202.5	127.5	98.5	224.5	1.0
SILVYN® AFW-PA black																
SILVYN AF W-PA	Lapp 5 50010 93	70 - 90°- angle	94.0	96.0	60.5	80.5	96.4	69	70.0	56.5	6.2	152.5	103.5	81.5	175.0	1.0
SILVYN AF W-PA	Lapp 5 50010 92	95 - 90°- angle	128.0	126.0	74.0	108.0	123.5	96	95.0	55.0	7.0	202.5	127.5	98.5	224.5	1.0