



Description: SILVYN AMHW-M_
Lapp code: Lapp 55503255

The **Test voltage** of the cable Lapp 55503255 is /.

Application range

- In combination with protective conduit:
- SILVYN® HTDL/EF/OR/HCX/HFX/FG HIPROJACKET
- Mechanical engineering
- Railway applications

Product Make-up

- Metric connection thread
- 45° elbow, hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 55503255 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Anamet designation	SW (mm)	Suitable for SILVYN® HTDL/EF/ OR/HCX/HFX	Pieces / PU
SILVYN® AMHW-M 45°						
SILVYN AMHW-M	Lapp 55503250	16 x 1,5	812.416.1	26	3/8"	50.0
SILVYN AMHW-M	Lapp 55503251	20 x 1,5	812.420.1	29	1/2"	50.0
SILVYN AMHW-M	Lapp 55503252	25 x 1,5	812.425.1	35	3/4"	25.0
SILVYN AMHW-M	Lapp 55503253	32 x 1,5	812.432.1	45	1."	10.0
SILVYN AMHW-M	Lapp 55503254	40 x 1,5	812.440.1	54	1 1/4"	5.0
SILVYN AMHW-M	Lapp 55503255	50 x 1,5	812.450.1	62	1 1/2"	5.0
SILVYN AMHW-M	Lapp 55503256	63 x 1,5	812.463.1	77	2."	4.0