



Description: SILVYN AMW-M_

Lapp code: Lapp 55503261

The **Test voltage** of the cable Lapp 55503261 is /.

Application range

- In combination with protective conduit:
- SILVYN® HTDL/EF/OR/HCX/HFX/FG HIPROJACKET
- Mechanical engineering
- Railway applications

Product Make-up

- Metric connection thread
- 90° hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 55503261 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | Anamet designation | SW (mm) | Suitable for SILVYN® HTDL/EF/ OR/HCX/HFX | Pieces / PU |
|-------------------|---------------|---------------------|--------------------|---------|--|-------------|
| SILVYN® AMW-M 90° | | | | | | |
| SILVYN AMW-M | Lapp 55503260 | 16 x 1,5 | 812.916.1 | 26 | 3/8" | 50.0 |
| SILVYN AMW-M | Lapp 55503261 | 20 x 1,5 | 812.920.1 | 29 | 1/2" | 50.0 |
| SILVYN AMW-M | Lapp 55503262 | 25 x 1,5 | 812.925.1 | 35 | 3/4" | 25.0 |
| SILVYN AMW-M | Lapp 55503263 | 32 x 1,5 | 812.932.1 | 45 | 1." | 10.0 |
| SILVYN AMW-M | Lapp 55503264 | 40 x 1,5 | 812.940.1 | 54 | 1 1/4" | 5.0 |
| SILVYN AMW-M | Lapp 55503265 | 50 x 1,5 | 812.950.1 | 62 | 1 1/2" | 5.0 |
| SILVYN AMW-M | Lapp 55503266 | 63 x 1,5 | 812.963.1 | 77 | 2." | 4.0 |