



Description: SILVYN AMW-M_
Lapp code: Lapp 55503263

The **Test voltage** of the cable Lapp 55503263 is /.

Application range

- In combination with protective conduit:
- SILVYN® HTDL/EF/OR/HCX/HFX/FG HIPROJACKET
- Mechanical engineering
- Railway applications

Product Make-up

- Metric connection thread
- 90° hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 55503263 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Anamet designation	SW (mm)	Suitable for SILVYN® HTDL/EF/ OR/HCX/HFX	Pieces / PU
SILVYN® AMW-M 90°						
SILVYN AMW-M	Lapp 55503260	16 x 1,5	812.916.1	26	3/8"	50.0
SILVYN AMW-M	Lapp 55503261	20 x 1,5	812.920.1	29	1/2"	50.0
SILVYN AMW-M	Lapp 55503262	25 x 1,5	812.925.1	35	3/4"	25.0
SILVYN AMW-M	Lapp 55503263	32 x 1,5	812.932.1	45	1."	10.0
SILVYN AMW-M	Lapp 55503264	40 x 1,5	812.940.1	54	1 1/4"	5.0
SILVYN AMW-M	Lapp 55503265	50 x 1,5	812.950.1	62	1 1/2"	5.0
SILVYN AMW-M	Lapp 55503266	63 x 1,5	812.963.1	77	2."	4.0