



SILVYN® US-AS

**Description:** SILVYN AS 48\_  
**Lapp code:** Lapp 61802170

The **Test voltage** of the cable Lapp 61802170 is /.

## Application range

- Automation technology
- Mechanical engineering
- Plant engineering
- Rolling stock
- Applications with high mechanical stress

## Product Make-up

- Spirally-wound metal protective conduit with roughened profile

In our Cable list on next page you can find all interesting information acc. article Lapp 61802170 and much more.

**CABLE LIST - all informations you need you can find here**

Product Name	Lapp Nr.	PG size	Internal Ø x external Ø (mm)	Bending radius (mm)	Inner Ø (mm)	Suitable for SILVYN® MSK-M	Suitable for SILVYN® US-M	Suitable for SILVYN® US /US-EDU-AS/US MS-DR	PU ring (m)
SILVYN® AS									
SILVYN AS 7	Lapp 61802080	7	8 x 10	28	8	12 x 1,5	10 x 1,0	7	50.0
SILVYN AS 9	Lapp 61802090	9	11 x 14	34	11	16 x 1,5	12 x 1,5	9	50.0
SILVYN AS 11	Lapp 61802100	11	14 x 17	40	14	20 x 1,5	16 x 1,5	11	50.0
SILVYN AS 13.5	Lapp 61802110	13.5	16 x 19	45	16			13,5	50.0
SILVYN AS 16	Lapp 61802120	16	18 x 21	50	18	25 x 1,5	20 x 1,5	16	50.0
SILVYN AS 21	Lapp 61802130	21	23 x 27	63	23	32 x 1,5	25 x 1,5	21	50.0
SILVYN AS 29	Lapp 61802140	29	31 x 36	85	31	40 x 1,5	32 x 1,5	29	25.0
SILVYN AS 36	Lapp 61802150	36	40 x 45	100	40	50 x 1,5	40 x 1,5	36	25.0
SILVYN AS 48	Lapp 61802170	48	51 x 56	125	51	63 x 1,5	50 x 1,5	48	25.0