



SILVYN® US-AS

Description: SILVYN AS 7_
Lapp code: Lapp 61802080

The **Test voltage** of the cable Lapp 61802080 is /.

Application range

- Automation technology
- Mechanical engineering
- Plant engineering
- Rolling stock
- Applications with high mechanical stress

Product Make-up

- Spirally-wound metal protective conduit with roughened profile

In our Cable list on next page you can find all interesting information acc. article Lapp 61802080 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | PG size | Internal Ø x external Ø (mm) | Bending radius (mm) | Inner Ø (mm) | Suitable for SILVYN® MSK-M | Suitable for SILVYN® US-M | Suitable for SILVYN® US /US-EDU-AS/US MS-DR | PU ring (m) |
|----------------|---------------|---------|------------------------------|---------------------|--------------|----------------------------|---------------------------|---|-------------|
| SILVYN® AS | | | | | | | | | |
| SILVYN AS 7 | Lapp 61802080 | 7 | 8 x 10 | 28 | 8 | 12 x 1,5 | 10 x 1,0 | 7 | 50.0 |
| SILVYN AS 9 | Lapp 61802090 | 9 | 11 x 14 | 34 | 11 | 16 x 1,5 | 12 x 1,5 | 9 | 50.0 |
| SILVYN AS 11 | Lapp 61802100 | 11 | 14 x 17 | 40 | 14 | 20 x 1,5 | 16 x 1,5 | 11 | 50.0 |
| SILVYN AS 13.5 | Lapp 61802110 | 13.5 | 16 x 19 | 45 | 16 | | | 13,5 | 50.0 |
| SILVYN AS 16 | Lapp 61802120 | 16 | 18 x 21 | 50 | 18 | 25 x 1,5 | 20 x 1,5 | 16 | 50.0 |
| SILVYN AS 21 | Lapp 61802130 | 21 | 23 x 27 | 63 | 23 | 32 x 1,5 | 25 x 1,5 | 21 | 50.0 |
| SILVYN AS 29 | Lapp 61802140 | 29 | 31 x 36 | 85 | 31 | 40 x 1,5 | 32 x 1,5 | 29 | 25.0 |
| SILVYN AS 36 | Lapp 61802150 | 36 | 40 x 45 | 100 | 40 | 50 x 1,5 | 40 x 1,5 | 36 | 25.0 |
| SILVYN AS 48 | Lapp 61802170 | 48 | 51 x 56 | 125 | 51 | 63 x 1,5 | 50 x 1,5 | 48 | 25.0 |