



Description: SILVYN BMC-M_
Lapp code: Lapp 55510010

The **Test voltage** of the cable Lapp 55510010 is /.

Application range

- In combination with protective conduit
- All metric conduit glands

/

In our Cable list on next page you can find all interesting information acc. article Lapp 55510010 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | Connection thread M | Outer Ø (mm) | Overall length/ C (mm) | SW (mm) | Pieces / PU |
|---------------|---------------|---------------------|---------------------|--------------|------------------------|---------|-------------|
| SILVYN® BMC-M | | | | | | | |
| SILVYN BMC-M | Lapp 55510000 | 16 | M16 x 1.5 | 22.0 | 22.5 | 20 | 10.0 |
| SILVYN BMC-M | Lapp 55510010 | 20 | M20 x 1.5 | 26,4 | 25.0 | 24 | 10.0 |
| SILVYN BMC-M | Lapp 55510020 | 25 | M25 x 1.5 | 31,9 | 30.0 | 29 | 10.0 |
| SILVYN BMC-M | Lapp 55510030 | 32 | M32 x 1.5 | 38,5 | 32.5 | 35 | 10.0 |
| SILVYN BMC-M | Lapp 55510040 | 40 | M40 x 1.5 | 53.0 | 34.0 | 48 | 2.0 |
| SILVYN BMC-M | Lapp 55510050 | 50 | M50 x 1.5 | 63,8 | 38.0 | 58 | 1.0 |
| SILVYN BMC-M | Lapp 55510060 | 63 | M63 x 1.5 | 77.0 | 45.0 | 70 | 1.0 |