



Description: SILVYN BW-M_

Lapp code: Lapp 55000531

The **Test voltage** of the cable Lapp 55000531 is /.

Application range

- Mechanical engineering
- Plant engineering
- Control cabinet manufacturing
- Used in areas where SILVYN® protective conduits cannot be inserted into a machine or an appliance

Product Make-up

- Steel fixing bracket
- 2 x bore hole for fixation

In our Cable list on next page you can find all interesting information acc. article Lapp 55000531 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | A [mm] | B in mm | Overall length/ C (mm) | D (mm) | E mm | Pieces / PU |
|--------------|---------------|---------------------|--------|---------|---------------------------|--------|------|-------------|
| SILVYN® BW-M | | | | | | | | |
| SILVYN BW-M | Lapp 55000531 | 16 | 20.0 | 50.0 | 33.2 | 40.0 | 17.0 | 25.0 |
| SILVYN BW-M | Lapp 55000541 | 20 | 20.0 | 50.0 | 38.0 | 40.0 | 21.0 | 25.0 |
| SILVYN BW-M | Lapp 55000551 | 25 | 20.0 | 60.0 | 46.9 | 50.0 | 26.0 | 25.0 |
| SILVYN BW-M | Lapp 55000561 | 32 | 20.0 | 70.0 | 56.9 | 60.0 | 33.0 | 25.0 |
| SILVYN BW-M | Lapp 55000571 | 40 | 20.0 | 80.0 | 67.0 | 70.0 | 41.0 | 25.0 |
| SILVYN BW-M | Lapp 55000572 | 50 | 20.0 | 90.0 | 78.4 | 80.0 | 51.0 | 25.0 |