



Description: SILVYN ELT 25 x 30,5_

Lapp code: Lapp 61751740

The **Test voltage** of the cable Lapp 61751740 is /.

Application range

- Mechanical engineering
- Machine tools
- Vending machine construction
- Applications with higher temperatures

Product Make-up

- Integrated hard PVC spiral
- Modified soft PVC sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 61751740 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Internal Ø x external Ø (mm)	Bending radius (mm)	Inner Ø (mm)	Suitable for SILVYN® MPC-M/MPC 90°M	Suitable for SILVYN® MPC	Suitable for SILVYN® MPC 90°	PU ring (m)
SILVYN® ELT								
SILVYN ELT 10 x 14,5	Lapp 61751700	10 x 14,5	25	10	16/1	9	9	30.0
SILVYN ELT 12 x 16,5	Lapp 61751710	12 x 16,5	25	12	16/2 , 20/1	11 , 13,5/1	11 , 13,5/1	30.0
SILVYN ELT 16 x 21	Lapp 61751720	16 x 21	35	16	20/2	13,5/2 , 16	13,5/2 , 16	30.0
SILVYN ELT 22 x 27,5	Lapp 61751730	22 x 27,5	45	22	25 x 1,5	21	21	30.0
SILVYN ELT 25 x 30,5	Lapp 61751740	25 x 30,5	55	25	32/1	29/1	29/1	30.0
SILVYN ELT 28 x 33,5	Lapp 61751750	28 x 33,5	60	28	32/2	29/2	29/2	30.0
SILVYN ELT 35 x 41	Lapp 61751760	35 x 41	80	35	40 x 1,5	36	36	30.0
SILVYN ELT 40 x 46,4	Lapp 61751770	40 x 46,4	105	40	50 x 1,5	42		30.0
SILVYN ELT 50 x 57	Lapp 61751780	50 x 57	120	50	63 x 1,5	48		30.0