



Description: **SILVYN EMC AS-CU_**
Lapp code: Lapp 64400502

The **Test voltage** of the cable Lapp 64400502 is /.

Application range

- Mechanical engineering
- Automotive industry
- Conveyor technology
- Railway applications / vehicle construction
- Used in areas where electromagnetic interferences can occur

Product Make-up

- Spirally-wound metal protective conduit with roughened profile
- Tinned-copper braiding

In our Cable list on next page you can find all interesting information acc. article Lapp 64400502 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Article IØ x OØ (mm)	Bending radius (mm)	Suitable for SILVYN® MSK-M	Suitable for SILVYN® US-M	Suitable for SILVYN® US/US-EDU-AS/US MS-DR	PU ring (m)
SILVYN® EMC AS-CU								
SILVYN EMC AS-CU	Lapp 64400500	SILVYN® EMC AS-CU 10	7 x 10	28	12 x 1,5	10 x 1,0	7	50
SILVYN EMC AS-CU	Lapp 64400501	SILVYN® EMC AS-CU 14	10 x 14	34	16 x 1,5	12 x 1,5	9	50
SILVYN EMC AS-CU	Lapp 64400502	SILVYN® EMC AS-CU 17	13 x 17	40	20 x 1,5	16 x 1,5	11	50
SILVYN EMC AS-CU	Lapp 64400503	SILVYN® EMC AS-CU 19	15 x 19	45			13,5	50
SILVYN EMC AS-CU	Lapp 64400504	SILVYN® EMC AS-CU 21	17 x 21	50	25 x 1,5	20 x 1,5	16	50
SILVYN EMC AS-CU	Lapp 64400505	SILVYN® EMC AS-CU 27	22 x 27	63	32 x 1,5	25 x 1,5	21	50
SILVYN EMC AS-CU	Lapp 64400506	SILVYN® EMC AS-CU 36	29 x 36	85	40 x 1,5	32 x 1,5	29	25
SILVYN EMC AS-CU	Lapp 64400507	SILVYN® EMC AS-CU 45	38 x 45	100	50 x 1,5	40 x 1,5	36	25
SILVYN EMC AS-CU	Lapp 64400508	SILVYN® EMC AS-CU 56	49 x 56	135	63 x 1,5	50 x 1,5	48	25