



Description: SILVYN FD-PU 16 x 21_

Lapp code: Lapp 64453700

The **Test voltage** of the cable Lapp 64453700 is /.

Application range

- For indoor and outdoor use
- Mechanical engineering
- In drag chains (SILVYN® CHAIN)
- Robot-building
- Moving applications

Product Make-up

- PVC-insulated steel spring wire
- PUR outer sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 64453700 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Internal Ø x external Ø (mm)	Bending radius (mm)	Inner Ø (mm)	Weight (kg/m)	Suitable for SILVYN® USK-M/US-M	Suitable for SILVYN® LKI-M/MSK-M	Suitable for SILVYN® USK/US/LKI/EE-K	PU ring (m)
SILVYN® FD-PU									
SILVYN FD-PU 7 x 10	Lapp 64453660	7 x 10	10	7	0.09	10 x 1,0	12 x 1,5	7	10.0
SILVYN FD-PU 10 x 14	Lapp 64453670	10 x 14	14	10	0.11	12 x 1,5	16 x 1,5	9	10.0
SILVYN FD-PU 13 x 17	Lapp 64453680	13 x 17	17	13	0.22	16 x 1,5	20 x 1,5	11	10.0
SILVYN FD-PU 15 x 19	Lapp 64453690	15 x 19	19	15	0.28			13,5	10.0
SILVYN FD-PU 16 x 21	Lapp 64453700	16 x 21	21	16	0.3	20 x 1,5	25 x 1,5	16	10.0
SILVYN FD-PU 22 x 27	Lapp 64453710	22 x 27	27	22	0.33	25 x 1,5	32 x 1,5	21	10.0
SILVYN FD-PU 29 x 36	Lapp 64453720	29 x 36	36	29	0.45	32 x 1,5	40 x 1,5	29	10.0
SILVYN FD-PU 38 x 45	Lapp 64453730	38 x 45	45	38	0.56	40 x 1,5	50 x 1,5	36	10.0
SILVYN FD-PU 48 x 56	Lapp 64453750	48 x 56	56	48	0.82	50 x 1,5	63 x 1,5	48	10.0