



Description: SILVYN FLEXILOK PG 21_

Lapp code: Lapp 68100090

The **Test voltage** of the cable Lapp 68100090 is /.

Application range

- Mechanical engineering
- Control cabinet manufacturing
- Moving applications
- Applications with limited space
- Building Installation

Product Make-up

- Connection thread metric/PG
- One-piece body
- Special clamping system

In our Cable list on next page you can find all interesting information acc. article Lapp 68100090 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Connection thread M	Inner Ø (mm)	Thread length/ D (mm)	Suitable for SILVYN® FPAS	Suitable for conduit ØØ (mm)	Pieces / PU
SILVYN® FLEXILOK PG black							
SILVYN FLEXILOK PG 9/1	Lapp 65500475	9/1	12	10.0	FPAS 13	13,0	10.0
SILVYN FLEXILOK PG 9/2	Lapp 65500495	9/2	12	10.0	FPAS 16	15,8	10.0
SILVYN FLEXILOK PG 11/1	Lapp 65500485	11/1	12	10.0	FPAS 13	13,0	10.0
SILVYN FLEXILOK PG 11/2	Lapp 65500395	11/2	15	10.0	FPAS 16	15,8	10.0
SILVYN FLEXILOK PG 13,5/1	Lapp 68100055	13,5/1	15	10.0	FPAS 16	15,8	10.0
SILVYN FLEXILOK PG 13,5/2	Lapp 68100075	13,5/2	16	10.0	FPAS 21	21,2	10.0
SILVYN FLEXILOK PG 16/1	Lapp 68100065	16/1	15	11.0	FPAS 16	15,8	10.0
SILVYN FLEXILOK PG 16/2	Lapp 68100085	16/2	18	11.0	FPAS 21	21,2	10.0
SILVYN FLEXILOK PG 21	Lapp 68100095	21	23	12.0	FPAS 28	28,5	10.0
SILVYN FLEXILOK PG 29	Lapp 68880005	29	31	12.0	FPAS 34	34,5	10.0
SILVYN® FLEXILOK PG grey							
SILVYN FLEXILOK PG 9/1	Lapp 65500470	9/1	12	10.0	FPAS 13	13,0	10.0
SILVYN FLEXILOK PG 9/2	Lapp 65500490	9/2	12	10.0	FPAS 16	15,8	10.0
SILVYN FLEXILOK PG 11/1	Lapp 65500480	11/1	12	10.0	FPAS 13	13,0	10.0
SILVYN FLEXILOK PG 11/2	Lapp 65500390	11/2	15	10.0	FPAS 16	15,8	10.0
SILVYN FLEXILOK PG 13,5/1	Lapp 68100050	13,5/1	15	10.0	FPAS 16	15,8	10.0
SILVYN FLEXILOK PG 16/1	Lapp 68100060	16/1	15	11.0	FPAS 16	15,8	10.0
SILVYN FLEXILOK PG 16/2	Lapp 68100080	16/2	18	11.0	FPAS 21	21,2	10.0
SILVYN FLEXILOK PG 21	Lapp 68100090	21	23	12.0	FPAS 28	28,5	10.0

SILVYN FLEXILOK PG 21_

Lapp 68100090



Product Name	Lapp Nr.	Connection thread M	Inner Ø (mm)	Thread length/ D (mm)	Suitable for SILVYN® FPAS	Suitable for conduit ØØ (mm)	Pieces / PU
SILVYN FLEXILOK PG 29	Lapp 65500620	29	31	12.0	FPAS 34	34,5	10.0