



Description: SILVYN FPAG-M_
Lapp code: Lapp 55506320

The **Test voltage** of the cable Lapp 55506320 is /.

Application range

- In combination with protective conduit:
- SILVYN® FPAS
- Applications with strong vibrations

Product Make-up

- Metric connection thread
- Upper part with integrated all-round tothing

In our Cable list on next page you can find all interesting information acc. article Lapp 55506320 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	For conduit with outer Ø (mm)	Suitable for SILVYN® FPAS	Pieces / PU
SILVYN® FPAG-M black					
SILVYN FPAG-M	Lapp 55506305	M12x1,5	10,0	10	10,0
SILVYN FPAG-M	Lapp 55506315	M16x1,5/1	13,0	13	10,0
SILVYN FPAG-M	Lapp 55506325	M16x1,5/2	15,8	16	10,0
SILVYN FPAG-M	Lapp 55506335	M20x1,5/1	15,8	16	10,0
SILVYN FPAG-M	Lapp 55506345	M20x1,5/2	21,2	21	10,0
SILVYN FPAG-M	Lapp 55507055	M20x1,5/3	18,5	18	10,0
SILVYN FPAG-M	Lapp 55506355	M25x1,5	28,5	28	10,0
SILVYN FPAG-M	Lapp 55506365	M32x1,5	34,5	34	10,0
SILVYN FPAG-M	Lapp 55506375	M40x1,5	42,5	42	2,0
SILVYN FPAG-M	Lapp 55506385	M50x1,5/1	42,5	42	2,0
SILVYN FPAG-M	Lapp 55506395	M50x1,5/2	54,5	54	2,0
SILVYN FPAG-M	Lapp 55506405	M63x1,5/1	54,5	54	2,0
SILVYN FPAG-M	Lapp 55506475	M63x1,5/2	67,2	67	2,0
SILVYN® FPAG-M grey					
SILVYN FPAG-M	Lapp 55506300	M12x1,5	10,0	10	10,0
SILVYN FPAG-M	Lapp 55506310	M16x1,5/1	13,0	13	10,0
SILVYN FPAG-M	Lapp 55506320	M16x1,5/2	15,8	16	10,0
SILVYN FPAG-M	Lapp 55506330	M20x1,5/1	15,8	16	10,0
SILVYN FPAG-M	Lapp 55506340	M20x1,5/2	21,2	21	10,0
SILVYN FPAG-M	Lapp 55507050	M20x1,5/3	18,5	18	10,0
SILVYN FPAG-M	Lapp 55506350	M25x1,5	28,5	28	10,0
SILVYN FPAG-M	Lapp 55506360	M32x1,5	34,5	34	10,0
SILVYN FPAG-M	Lapp 55506370	M40x1,5	42,5	42	2,0
SILVYN FPAG-M	Lapp 55506380	M50x1,5/1	42,5	42	2,0
SILVYN FPAG-M	Lapp 55506390	M50x1,5/2	54,5	54	2,0
SILVYN FPAG-M	Lapp 55506400	M63x1,5/1	54,5	54	2,0
SILVYN FPAG-M	Lapp 55506470	M63x1,5/2	67,2	67	2,0