



**Description:** SILVYN KLICK 90° PG\_

**Lapp code:** Lapp 61801050

The **Test voltage** of the cable Lapp 61801050 is /.

## Application range

- In combination with protective conduit:
- SILVYN® RILL PA6
- SILVYN® RILL PA12
- For applications with limited space
- Rotating applications

## Product Make-up

- PG connection thread
- 90° elbow
- Body with inner sealing
- Upper part with snap-in sleeve

In our Cable list on next page you can find all interesting information acc. article Lapp 61801050 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Suitable for SILVYN® RILL	For conduit with outer Ø (mm)	Thread length (mm)	Clear opening (mm)	Pieces / PU
SILVYN® KLICK 90° PG grey							
SILVYN KLICK 90° PG	Lapp 61801020	9	9	13	10	12.0	50
SILVYN KLICK 90° PG	Lapp 61801030	11	11	15,8	10	15.5	50
SILVYN KLICK 90° PG	Lapp 56000100	13,5	13,5	18,5	11	13.5	50
SILVYN KLICK 90° PG	Lapp 61801040	16	16	21,2	12	18.0	50
SILVYN KLICK 90° PG	Lapp 61801050	21	21	28,5	12	24.0	25
SILVYN KLICK 90° PG	Lapp 61801060	29	29	34,5	12	32.0	10
SILVYN KLICK 90° PG	Lapp 61801061	36	36	42,5	14	36.5	10
SILVYN KLICK 90° PG	Lapp 61801062	48	48	54,5	14	48.5	5
SILVYN® KLICK 90° PG black							
SILVYN KLICK 90° PG	Lapp 61801025	9	9	13	10	12.0	50
SILVYN KLICK 90° PG	Lapp 61801035	11	11	15,8	10	15.5	50
SILVYN KLICK 90° PG	Lapp 56000105	13,5	13,5	18,5	11	13.5	50
SILVYN KLICK 90° PG	Lapp 61801045	16	16	21,2	12	18.0	50
SILVYN KLICK 90° PG	Lapp 61801055	21	21	28,5	12	24.0	25
SILVYN KLICK 90° PG	Lapp 61801065	29	29	34,5	12	32.0	10