



Description: SILVYN KLICK-GP_
Lapp code: Lapp 61800905

The **Test voltage** of the cable Lapp 61800905 is /.

Application range

- In combination with protective conduit:
- SILVYN® RILL PA6
- SILVYN® RILL PA12
- Robot-building
- Rotating applications

Product Make-up

- PG connection thread
- Body with inner sealing
- Upper part with snap-in sleeve

In our Cable list on next page you can find all interesting information acc. article Lapp 61800905 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Suitable for SILVYN® RILL	For conduit with outer Ø (mm)	Wrench size (mm)	Thread length (mm)	Hole (mm)	Pieces / PU
SILVYN® KLICK-GP grey								
SILVYN KLICK-GP	Lapp 61800860	7	7	10	15.5	10	7	50
SILVYN KLICK-GP	Lapp 61800870	9	9	13	18.0	10	10	50
SILVYN KLICK-GP	Lapp 61800880	11	11	15,8	21.0	10	12.5	50
SILVYN KLICK-GP	Lapp 61800850	13,5	13,5	18,2	24.0	11	13.5	50
SILVYN KLICK-GP	Lapp 61800890	16	16	21,2	27.0	12	17	50
SILVYN KLICK-GP	Lapp 61800900	21	21	28,5	34.0	12	23.5	25
SILVYN KLICK-GP	Lapp 61800910	29	29	34,5	40.0	12	30.5	25
SILVYN KLICK-GP	Lapp 61800920	36	36	42,5	49.0	12	36.5	25
SILVYN KLICK-GP	Lapp 61800930	48	48	54,5	60.0	15	48.5	10
SILVYN® KLICK-GP black								
SILVYN KLICK-GP	Lapp 61800865	7	7	10	15.5	10	7	50
SILVYN KLICK-GP	Lapp 61800875	9	9	13	18.0	10	10	50
SILVYN KLICK-GP	Lapp 61800885	11	11	15,8	21.0	10	12.5	50
SILVYN KLICK-GP	Lapp 61800855	13,5	13,5	18,2	24.0	11	13.5	50
SILVYN KLICK-GP	Lapp 61800895	16	16	21,2	27.0	12	17	50
SILVYN KLICK-GP	Lapp 61800905	21	21	28,5	34.0	12	23.5	25
SILVYN KLICK-GP	Lapp 61800915	29	29	34,5	40.0	12	30.5	25
SILVYN KLICK-GP	Lapp 61800925	36	36	42,5	49.0	12	36.5	25
SILVYN KLICK-GP	Lapp 61800935	48	48	54,5	60.0	15	48.5	10