



Description: SILVYN KLICK-GPZ_
Lapp code: Lapp 61801135

The **Test voltage** of the cable Lapp 61801135 is /.

Application range

- In combination with protective conduit:
- SILVYN® RILL PA6
- SILVYN® RILL PA12
- Robot-building
- Used in areas where cables and wires need to be provided with strain relief and additional sealing

Product Make-up

- PG connection thread
- Cable gland
- Body with inner sealing
- Upper part with snap-in sleeve

In our Cable list on next page you can find all interesting information acc. article Lapp 61801135 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | Suitable for SILVYN® RILL | For conduit with outer Ø (mm) | Wrench size (mm) | Clamping range (mm) | Thread length (mm) | min. IØ (mm) | Pieces / PU |
|-------------------------|---------------|---------------------|---------------------------|-------------------------------|------------------|---------------------|--------------------|--------------|-------------|
| SILVYN® KLICK-GPZ grey | | | | | | | | | |
| SILVYN KLICK-GPZ | Lapp 61801120 | 7 | 7 | 10 | 16.0 | 3 - 6,5 | 8 | 7.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801130 | 9 | 9 | 13 | 18.0 | 4 - 8 | 8 | 8.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801140 | 11 | 11 | 15,8 | 21.0 | 5 - 10 | 8 | 10.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801200 | 13,5/1 | 11 | 15,8 | 27.0 | 6 - 11 | 8 | 12.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801202 | 13,5/2 | 13,5 | 18,5 | 27.0 | 6 - 12 | 8 | 12.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801150 | 16 | 16 | 21,2 | 27.0 | 10 - 14 | 10 | 14.0 | 10 |
| SILVYN KLICK-GPZ | Lapp 61801160 | 21 | 21 | 28,5 | 34.0 | 13 - 18 | 11 | 18.0 | 10 |
| SILVYN KLICK-GPZ | Lapp 61801170 | 29 | 29 | 34,5 | 40.0 | 18 - 25 | 12 | 25.0 | 10 |
| SILVYN KLICK-GPZ | Lapp 61801180 | 36 | 36 | 42,5 | 49.0 | 22 - 32 | 13 | 32.0 | 10 |
| SILVYN KLICK-GPZ | Lapp 61801190 | 48 | 48 | 54,5 | 60.0 | 34 - 44 | 14 | 44.0 | 10 |
| SILVYN® KLICK-GPZ black | | | | | | | | | |
| SILVYN KLICK-GPZ | Lapp 61801125 | 7 | 7 | 10 | 16.0 | 3 - 6,5 | 8 | 7.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801135 | 9 | 9 | 13 | 18.0 | 4 - 8 | 8 | 8.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801145 | 11 | 11 | 15,8 | 21.0 | 5 - 10 | 8 | 10.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801205 | 13,5/1 | 11 | 15,8 | 27.0 | 6 - 11 | 8 | 11.0 | 20 |
| SILVYN KLICK-GPZ | Lapp 61801155 | 16 | 16 | 21,2 | 27.0 | 10 - 14 | 10 | 14.0 | 10 |
| SILVYN KLICK-GPZ | Lapp 61801165 | 21 | 21 | 28,5 | 34.0 | 13 - 18 | 11 | 18.0 | 10 |
| SILVYN KLICK-GPZ | Lapp 61801175 | 29 | 29 | 34,5 | 40.0 | 18 - 25 | 12 | 25.0 | 10 |
| SILVYN KLICK-GPZ | Lapp 61801185 | 36 | 36 | 42,5 | 49.0 | 22 - 32 | 13 | 32.0 | 10 |
| SILVYN KLICK-GPZ | Lapp 61801195 | 48 | 48 | 54,5 | 60.0 | 34 - 44 | 14 | 44.0 | 10 |