



Description: SILVYN LCC-2_
Lapp code: Lapp 61804762

The **Test voltage** of the cable Lapp 61804762 is /.

Application range

- Mechanical engineering
- Plant engineering
- Outdoors
- Used in areas where liquids are present
- Applications with high mechanical stress

Product Make-up

- Spirally-wound metal protective conduit with roughened profile
- PVC sheath

In our Cable list on next page you can find all interesting information acc. article Lapp 61804762 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Internal Ø x external Ø (mm)	Bending radius (mm)	Inner Ø (mm)	Suitable for SILVYN® LGF-2-M/LGS-2-M	Suitable for SILVYN® LGS-2	PU ring (m)
SILVYN® LCC-2								
SILVYN LCC-2	Lapp 61804702	LCC-2/10	6,8 x 10	25	6.8	M12x1,5	7	30.0
SILVYN LCC-2	Lapp 61804712	LCC-2/12	10 x 14,2	30	10	M16x1,5/1	9	30.0
SILVYN LCC-2	Lapp 61804722	LCC-2/16	12,9 x 17,1	40	12.9	M16x1,5/2 + M20x1,5/1	11	30.0
SILVYN LCC-2	Lapp 61804732	LCC-2/20	16,8 x 21,6	45	16.8	M20x1,5/2	13,5 + 16	30.0
SILVYN LCC-2	Lapp 61804742	LCC-2/25	20,9 x 26	55	20.9	M25x1,5	21	30.0
SILVYN LCC-2	Lapp 61804752	LCC-2/32	27,8 x 34	60	27.8	M32x1,5	29	30.0
SILVYN LCC-2	Lapp 61804762	LCC-2/40	37,6 x 44,5	80	37.6	M40x1,5	36	10.0
SILVYN LCC-2	Lapp 61804772	LCC-2/50	48,4 x 55	90	48.4	M50x1,5		10.0
SILVYN LCC-2	Lapp 61804792	LCC-2/63	57,5 x 64,5	115	57.5	M63x1,5	48	10.0