



Description: SILVYN LCG-M_
Lapp code: Lapp 55503225

The **Test voltage** of the cable Lapp 55503225 is /.

Application range

- In combination with protective conduit
- SILVYN® LCC-2 / LCCH-2
- Applications with high mechanical stress
- Used in areas where liquids are present

Product Make-up

- Metric connection thread
- Hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 55503225 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Overall length/ C (mm)	Thread length/ D (mm)	SW 1/2 mm	Suitable for SILVYN® LCC-2/LCCH-2	Pieces / PU
SILVYN® LCG-M							
SILVYN LCG-M	Lapp 55503220	12 x 1,5	29.8	10.0	20 / 20	10	10.0
SILVYN LCG-M	Lapp 55503221	16 x 1,5/1	29.8	10.0	22 / 24	12	10.0
SILVYN LCG-M	Lapp 55503222	16 x 1,5/2	33.0	12.0	24 / 26	16	10.0
SILVYN LCG-M	Lapp 55503223	20 x 1,5/1	33.0	12.0	24 / 26	16	10.0
SILVYN LCG-M	Lapp 55503224	20 x 1,5/2	33.5	12.0	26 / 29	20	10.0
SILVYN LCG-M	Lapp 55503225	25 x 1,5	40.5	14.0	33 / 35	25	10.0
SILVYN LCG-M	Lapp 55503226	32 x 1,5	45.8	15.0	40 / 42	32	2.0
SILVYN LCG-M	Lapp 55503227	40 x 1,5	47.5	16.0	56 / 58	40	1.0
SILVYN LCG-M	Lapp 55503228	50 x 1,5	51.0	16.0	70 / 70	50	1.0