



Description: SILVYN LKI-M 63 x 1.5_

Lapp code: Lapp 55501470

The **Test voltage** of the cable Lapp 55501470 is /.

Application range

- In combination with protective conduit:
- SILVYN® FPS
- SILVYN® FD-PU
- Robot-building
- For rotating applications

Product Make-up

- Metric connection thread
- Swivelling upper part with integrated inner sleeve

In our Cable list on next page you can find all interesting information acc. article Lapp 55501470 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Connection thread M | Clear opening (mm) | Overall length/ C (mm) | Thread length/ D (mm) | SW (mm) | Suitable for SILVYN® FPS/FD-PU | Pieces / PU |
|-----------------------|---------------|---------------------|--------------------|------------------------|-----------------------|---------|--------------------------------|-------------|
| SILVYN® LKI-M | | | | | | | | |
| SILVYN LKI-M 12 x 1.5 | Lapp 55501400 | 12 x 1.5 | 5.5 | 38.0 | 10.0 | 16 | 7 x 10 | 50.0 |
| SILVYN LKI-M 16 x 1.5 | Lapp 55501410 | 16 x 1.5 | 9.5 | 39.5 | 10.0 | 19 | 10 x 14 | 50.0 |
| SILVYN LKI-M 20 x 1.5 | Lapp 55501420 | 20 x 1.5 | 11.5 | 42.0 | 10.0 | 22 | 13 x 17 | 50.0 |
| SILVYN LKI-M 25 x 1.5 | Lapp 55501430 | 25 x 1.5 | 14.5 | 48.0 | 11.0 | 27 | 16 x 21 | 50.0 |
| SILVYN LKI-M 32 x 1.5 | Lapp 55501440 | 32 x 1.5 | 19.5 | 58.0 | 12.0 | 35 | 22 x 27 | 25.0 |
| SILVYN LKI-M 40 x 1.5 | Lapp 55501450 | 40 x 1.5 | 27.0 | 59.0 | 12.0 | 45 | 29 x 36 | 25.0 |
| SILVYN LKI-M 50 x 1.5 | Lapp 55501460 | 50 x 1.5 | 35.5 | 62.5 | 12.0 | 54 | 38 x 45 | 25.0 |
| SILVYN LKI-M 63 x 1.5 | Lapp 55501470 | 63 x 1.5 | 46.0 | 68.0 | 15.0 | 65 | 48 x 56 | 10.0 |