



**Description:** SILVYN LTPG-M\_  
**Lapp code:** Lapp 55510250

The **Test voltage** of the cable Lapp 55510250 is /.

## Application range

- In combination with protective conduit:
- SILVYN® LTP
- Applications with high mechanical stress
- Used in areas where liquids are present

## Product Make-up

- Metric connection thread
- Hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 55510250 and much more.

**CABLE LIST - all informations you need you can find here**

Product Name	Lapp Nr.	Article designation	Overall length/ C (mm)	Thread length/ D (mm)	SW 1/2 mm	Suitable for SILVYN® LTP	Pieces / PU
SILVYN® LTPG-M							
SILVYN LTPG-M	Lapp 55510200	M12 x 1,5	29.8	10.0	20 / 20	10	10.0
SILVYN LTPG-M	Lapp 55510210	M16 x 1,5/1	29.8	10.0	20 / 22	12	10.0
SILVYN LTPG-M	Lapp 55510220	M16 x 1,5/2	33.0	10.0	24 / 26	16	10.0
SILVYN LTPG-M	Lapp 55510230	M20 x 1,5/1	33.0	12.0	24 / 26	16	10.0
SILVYN LTPG-M	Lapp 55510240	M20 x 1,5/2	33.5	12.0	26 / 29	20	10.0
SILVYN LTPG-M	Lapp 55510250	M25 x 1,5	40.5	14.0	33 / 35	25	10.0
SILVYN LTPG-M	Lapp 55510260	M32 x 1,5	45.8	15.0	40 / 42	32	2.0
SILVYN LTPG-M	Lapp 55510270	M40 x 1,5	47.5	16.0	50 / 52	40	1.0
SILVYN LTPG-M	Lapp 55510280	M50 x 1,5	51.0	16.0	58 / 58	50	1.0
SILVYN LTPG-M	Lapp 55510290	M 63 x 1,5	58.8	20.0	70 / 70	63	1.0