



**Description:** SILVYN LTPW-M\_  
**Lapp code:** Lapp 55510450

The **Test voltage** of the cable Lapp 55510450 is /.

## Application range

- In combination with protective conduit:
- SILVYN® LTP
- Applications with high mechanical stress
- Used in areas where liquids are present

## Product Make-up

- Metric connection thread
- 90° hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 55510450 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Thread length/ D (mm)	SW 1/2 mm	Suitable for SILVYN® LTP	Pieces / PU
SILVYN® LTPW-M						
SILVYN LTPW-M	Lapp 55510400	M16 x 1,5/1	10.0	20 / 24	12	10.0
SILVYN LTPW-M	Lapp 55510410	M16 x 1,5/2	10.0	20 / 26	16	10.0
SILVYN LTPW-M	Lapp 55510420	M20 x 1,5/1	13.0	24 / 26	16	10.0
SILVYN LTPW-M	Lapp 55510430	M20 x 1,5/2	13.0	24 / 29	20	10.0
SILVYN LTPW-M	Lapp 55510440	M25 x 1,5	14.0	30 / 35	25	10.0
SILVYN LTPW-M	Lapp 55510450	M32 x 1,5	15.0	36 / 42	32	2.0
SILVYN LTPW-M	Lapp 55510460	M40 x 1,5	18.0	46 / 52	40	1.0
SILVYN LTPW-M	Lapp 55510470	M50 x 1,5	18.0	57 / 58	50	1.0
SILVYN LTPW-M	Lapp 55510480	M 63 x 1,5	20.0	72 / 70	63	1.0