



**Description:** **SILVYN MPC 90°\_**  
**Lapp code:** Lapp 55502375

The **Test voltage** of the cable Lapp 55502375 is /.

## Application range

- In combination with protective conduit:
- SILVYN® SI/SP/SP-PU (smooth conduits)
- SILVYN® EL/ELÖ/ELT (corrugated conduits)

## Product Make-up

- PG connection thread
- 90° elbow with integrated conduit connection

In our Cable list on next page you can find all interesting information acc. article Lapp 55502375 and much more.

**CABLE LIST - all informations you need you can find here**

Product Name	Lapp Nr.	Article designation	PG size	Clear opening (mm)	Suitable for SILVYN® SI	Suitable for SILVYN® SP/SP-PU	SILVYN® EL/ELÖ/ELT	Pieces / PU
<b>SILVYN MPC 90° BK</b>								
SILVYN MPC 90°	Lapp 55502486	SILVYN MPC 90° PG 11 BK	11	10.5	13 x 16	12 x 16	12 x 16,6	10.0
SILVYN MPC 90°	Lapp 55502487	SILVYN MPC 90° PG 13,5 BK	13.5	10.5	13 x 16	12 x 16	12 x 16,6	10.0
SILVYN MPC 90°	Lapp 55502488	SILVYN MPC 90° PG 16 BK	16	14.5			16 x 20,7	10.0
SILVYN MPC 90°	Lapp 55502489	SILVYN MPC 90° PG 21 BK	21	19.0		16 x 20	22 x 27,7	10.0
SILVYN MPC 90°	Lapp 55502490	SILVYN MPC 90° PG 29 BK	29	24.5		16 x 20	28 x 33,5	10.0
SILVYN MPC 90°	Lapp 55502493	SILVYN MPC 90° PG 36 BK	36	33.0			35 x 41,0	2.0
<b>SILVYN® MPC 90° GY</b>								
SILVYN MPC 90°	Lapp 55502370	SILVYN MPC 90° PG 11 GY	11	10.5	13 x 16	12 x 16	12 x 16,6	10.0
SILVYN MPC 90°	Lapp 55502371	SILVYN MPC 90° PG 13,5 GY	13.5	10.5	13 x 16	12 x 16	12 x 16,6	10.0
SILVYN MPC 90°	Lapp 55502372	SILVYN MPC 90° PG 16 GY	16	14.5			16 x 20,7	10.0
SILVYN MPC 90°	Lapp 55502373	SILVYN MPC 90° PG 21 GY	21	19.0		16 x 20	22 x 27,7	10.0
SILVYN MPC 90°	Lapp 55502374	SILVYN MPC 90° PG 29 GY	29	24.5		16 x 20	28 x 33,5	10.0
SILVYN MPC 90°	Lapp 55502375	SILVYN MPC 90° PG 36 GY	36	33.0			35 x 41,0	2.0