



**Description:** **SILVYN MPC 90° M\_**  
**Lapp code:** Lapp 55502481

The **Test voltage** of the cable Lapp 55502481 is /.

## Application range

- In combination with protective conduit:
- SILVYN® SI/SP/SP-PU (smooth conduits)
- SILVYN® EL/ELÖ/ELT (corrugated conduits)

## Product Make-up

- Metric connection thread
- 90° elbow with integrated conduit connection

In our Cable list on next page you can find all interesting information acc. article Lapp 55502481 and much more.

**CABLE LIST - all informations you need you can find here**

Product Name	Lapp Nr.	Article designation	Connection thread M	Clear opening (mm)	Suitable for SILVYN® SI	Suitable for SILVYN® SP/SP-PU	SILVYN® EL/ELÖ/ELT	Pieces / PU
<b>SILVYN® MPC 90° M black</b>								
SILVYN MPC 90° M	Lapp 55502480	SILVYN MPC 90° M 16/1	16 x 1.5	10.5	13 x 16	12 x 16	12 x 16,6	10.0
SILVYN MPC 90° M	Lapp 55502481	SILVYN MPC 90° M 20/1	20 x 1.5	10.5	13 x 16	12 x 16	12 x 16,6	10.0
SILVYN MPC 90° M	Lapp 55502482	SILVYN MPC 90° M 20/2	20 x 1.5	14.5		16 x 20	16 x 20,7	10.0
SILVYN MPC 90° M	Lapp 55502483	SILVYN MPC 90° M 25	25 x 1.5	19.0		22 x 27	22 x 27,7	10.0
SILVYN MPC 90° M	Lapp 55502484	SILVYN MPC 90° M 32	32 x 1.5	24.5			28 x 33,5	10.0
SILVYN MPC 90° M	Lapp 55502485	SILVYN MPC 90° M 40	40 x 1.5	33.0			35 x 41,0	2.0
<b>SILVYN® MPC 90° M grey</b>								
SILVYN MPC 90° M	Lapp 55502458	SILVYN MPC 90° M 16/1	16 x 1.5	10.5	13 x 16	12 x 16	12 x 16,6	10.0
SILVYN MPC 90° M	Lapp 55502459	SILVYN MPC 90° M 20/1	20 x 1.5	10.5	13 x 16	12 x 16	12 x 16,6	10.0
SILVYN MPC 90° M	Lapp 55502366	SILVYN MPC 90° M 20/2	20 x 1.5	14.5		16 x 20	16 x 20,7	10.0
SILVYN MPC 90° M	Lapp 55502367	SILVYN MPC 90° M 25	25 x 1.5	19.0		22 x 27	22 x 27,7	10.0
SILVYN MPC 90° M	Lapp 55502368	SILVYN MPC 90° M 32	32 x 1.5	24.5			28 x 33,5	10.0
SILVYN MPC 90° M	Lapp 55502369	SILVYN MPC 90° M 40	40 x 1.5	33.0			35 x 41,0	2.0