



Description: SILVYN SSV 16_
Lapp code: Lapp 52003100

The **Test voltage** of the cable Lapp 52003100 is /.

Application range

- In combination with protective conduit:
- SILVYN® SI
- SILVYN® SP
- SILVYN® SP-PU

Product Make-up

- PG connection thread
- Conduit entry with special grip profile

In our Cable list on next page you can find all interesting information acc. article Lapp 52003100 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	PG size	Clear opening (mm)	Overall length/ C (mm)	Thread length/ D (mm)	SW (mm)	Suitable for SILVYN® SCH	Suitable for SILVYN® SI	Suitable for SILVYN® SP	Suitable for SILVYN® SP-PU	Pieces / PU
SILVYN® SSV											
SILVYN SSV 9	Lapp 52003070	9	8.0	25.0	5.5	19	10 - 16 S		10 x 14	10 x 14	100.0
SILVYN SSV 9	Lapp 53800020	9	10.0	25.0	5.5	19	12 - 20 S		12 x 16	12 x 16	100.0
SILVYN SSV 11	Lapp 52003080	11	12.0	25.0	6.0	22	16 - 25 S		14 x 18	14 x 18	50.0
SILVYN SSV 11	Lapp 52024560	11	14.0	25.0	6.0	22	16 - 25 S		16 x 20	16 x 20	50.0
SILVYN SSV 13.5	Lapp 52003090	13.5	15.5	27.5	6.5	25	20 - 32 S	18 x 22			50.0
SILVYN SSV 16	Lapp 52003100	16	19.0	27.5	7.5	30	20 - 32 S		22 x 27	22 x 27	25.0
SILVYN SSV 21	Lapp 52003110	21	21.0	30.0	8.0	32	20 - 32 S	23 x 28			25.0
SILVYN SSV 29	Lapp 53800080	29	27.0	33.0	9.5	40	25 - 40 S		30 x 36	30 x 36	25.0
SILVYN SSV 29	Lapp 52024640	29	30.0	33.0	9.5	42	32 - 50 S	32 x 38			25.0
SILVYN SSV 36	Lapp 52002980	36	34.0	37.0	12.0	52	32 - 50 S		38 x 44	38 x 44	10.0
SILVYN SSV 42	Lapp 52002990	42	41.0	41.0	14.0	57	40 - 60 S		45 x 51		5.0
SILVYN SSV 48	Lapp 52013000	48	46.0	44.0	14.0	64	40 - 60 S		50 x 56		5.0