



**Description:** SILVYN SSV-M 63 x 1.5\_

**Lapp code:** Lapp 52002847

The **Test voltage** of the cable Lapp 52002847 is /.

## Application range

- In combination with protective conduit:
- SILVYN® SI
- SILVYN® SP
- SILVYN® SP-PU

## Product Make-up

- Metric connection thread
- Conduit entry with special grip profile

In our Cable list on next page you can find all interesting information acc. article Lapp 52002847 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Connection thread M	Clear opening (mm)	Overall length/ C (mm)	Thread length/ D (mm)	SW (mm)	Suitable for SILVYN® SCH	Suitable for SILVYN® SI	Suitable for SILVYN® SP	Suitable for SILVYN® SP-PU	Pieces / PU
SILVYN® SSV-M											
SILVYN SSV-M 12 x 1.5/1	Lapp 52002827	12 x 1.5/1	7.0	25.0	8.0	16	10 - 16 S	7 x 9			50.0
SILVYN SSV-M 12 x 1.5/2	Lapp 52002828	12 x 1.5/2	9.0	25.0	8.0	19	10 - 16 S	9 x 12			50.0
SILVYN SSV-M 16 x 1.5/1	Lapp 52002840	16 x 1.5/1	8.0	25.0	8.0	19	10 - 16 S	11 x 14	10 x 14	10 x 14	50.0
SILVYN SSV-M 16 x 1.5/2	Lapp 52002839	16 x 1.5/2	10.0	25.0	8.0	19	12 - 20 S	13 x 16	12 x 16	12 x 16	50.0
SILVYN SSV-M 20 x 1.5/1	Lapp 52002841	20 x 1.5/1	12.0	25.0	8.0	22	16 - 25 S	14 x 18			50.0
SILVYN SSV-M 20 x 1.5/3	Lapp 52002842	20 x 1.5/3	15.5	25.0	8.0	25	20 - 32 S	18 x 23			50.0
SILVYN SSV-M 25x1.5	Lapp 52002843	25x1.5	19.0	29.5	8.5	32	20 - 32 S	23 x 28	22 x 27	22 x 27	25.0
SILVYN SSV-M 32 x 1.5	Lapp 52002844	32 x 1.5	27.0	32.5	9.5	40	32 - 50 S	32 x 38	30 x 36	30 x 36	25.0
SILVYN SSV-M 40x1.5	Lapp 52002845	40x1.5	34.0	36.0	11.0	50	32 - 50 S		38 x 44	38 x 44	10.0
SILVYN SSV-M 50 x 1.5	Lapp 52002846	50 x 1.5	41.0	39.0	12.0	57	40 - 60 S		45 x 51		5.0
SILVYN SSV-M 63 x 1.5	Lapp 52002847	63 x 1.5	46.0	43.0	12.0	67	40 - 60 S		50 x 56		5.0