



Description: SILVYN SSVZ-M 50 x 1.5_

Lapp code: Lapp 55501950

The **Test voltage** of the cable Lapp 55501950 is /.

Application range

- In combination with protective conduit:
- SILVYN® SI
- SILVYN® SP
- SILVYN® SP-PU

Product Make-up

- Metric connection thread
- Integrated cable gland
- Conduit entry with special grip profile

In our Cable list on next page you can find all interesting information acc. article Lapp 55501950 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Connection thread M	Clear opening (mm)	Overall length/ C (mm)	Thread length/ D (mm)	SW 1/2 mm	Suitable for SILVYN® SCH	Suitable for SILVYN® SI	Suitable for SILVYN® SP	Suitable for SILVYN® SP-PU	Pieces / PU
SILVYN® SSVZ-M											
SILVYN SSVZ-M 16 x 1.5/1	Lapp 55501850	16 x 1.5/1	8.0	39.0	5.0	19 / 18	10 - 16 S		10 x 14	10 x 14	50.0
SILVYN SSVZ-M 16 x 1.5/2	Lapp 55501860	16 x 1.5/2	10.0	39.0	5.0	19 / 18	12 - 20 S		12 x 16	12 x 16	50.0
SILVYN SSVZ-M 20 x 1.5/1	Lapp 55501870	20 x 1.5/1	12.0	39.6	6.0	22 / 22	16 - 25 S	14 x 18	14 x 18	14 x 18	50.0
SILVYN SSVZ-M 20 x 1.5/2	Lapp 55501880	20 x 1.5/2	12.5	39.6	6.0	22 / 22	16 - 25 S		16 x 20	16 x 20	50.0
SILVYN SSVZ-M 20 x 1.5/3	Lapp 55501890	20 x 1.5/3	15.5	43.0	6.0	25 / 22	20 - 32 S	18 x 23			50.0
SILVYN SSVZ-M 20 x 1.5/4	Lapp 55501900	20 x 1.5/4	16.0	44.0	6.0	30 / 24	20 - 32 S		22 x 27	22 x 27	25.0
SILVYN SSVZ-M 25 x 1.5	Lapp 55501910	25 x 1.5	20.0	48.0	7.0	32 / 30	20 - 32 S	23 x 28			25.0
SILVYN SSVZ-M 32 x 1.5/1	Lapp 55501920	32 x 1.5/1	27.0	53.6	8.0	40 / 40	25 - 40 S		30 x 36	30 x 36	25.0
SILVYN SSVZ-M 32 x 1.5/2	Lapp 55501930	32 x 1.5/2	30.0	53.6	8.0	42 / 40	32 - 50 S	32 x 38			25.0
SILVYN SSVZ-M 40 x 1.5	Lapp 55501940	40 x 1.5	34.0	61.6	8.0	52 / 50	32 - 50 S		38 x 44	38 x 44	10.0
SILVYN SSVZ-M 50 x 1.5	Lapp 55501950	50 x 1.5	41.0	68.6	9.0	57 / 57	40 - 60 S		45 x 51		5.0
SILVYN SSVZ-M 63 x 1.5	Lapp 55501960	63 x 1.5	46.0	71.6	10.0	64 / 66	40 - 60 S		50 x 56		5.0