



Description: SILVYN UI 511 -EG_
Lapp code: Lapp 61797926

The **Test voltage** of the cable Lapp 61797926 is /.

Application range

- In combination with protective conduit
- SILVYN® UI 511
- Offshore applications
- Outdoors
- Steel industry

Product Make-up

- Metric connection thread
- Hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 61797926 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | min. internal Ø | Overall length/ C (mm) | Thread length/ D (mm) | Internal Ø | SW (mm) | Suitable for SILVYN® UI 511 | Pieces / PU |
|--|---------------|---------------------|-----------------|------------------------|-----------------------|------------|---------|-----------------------------|-------------|
| SILVYN® UI 511 fitting (stainless steel) | | | | | | | | | |
| SILVYN UI 511 -EG | Lapp 61797918 | M 16 x 1,5/1 | 6.8 | 35.0 | 12.0 | 6.8 | 26 | 5/16" | 1.0 |
| SILVYN UI 511 -EG | Lapp 61797920 | M 16 x 1,5/2 | 9.8 | 35.0 | 12.0 | 9.8 | 26 | 3/8" | 1.0 |
| SILVYN UI 511 -EG | Lapp 61797926 | M 20 x 1,5/3 | 13.9 | 37.0 | 13.0 | 13.9 | 29 | 1/2" | 1.0 |
| SILVYN UI 511 -EG | Lapp 61797928 | M 25 x 1,5 | 18.5 | 40.0 | 15.0 | 18.5 | 35 | 3/4" | 1.0 |
| SILVYN UI 511 -EG | Lapp 61797930 | M 32 x 1,5 | 22.8 | 46.0 | 15.0 | 22.8 | 45 | 1." | 1.0 |
| SILVYN UI 511 -EG | Lapp 61797932 | M 40 x 1,5 | 30.8 | 52.0 | 16.0 | 30.8 | 54 | 1 1/4" | 1.0 |