



**Description:** SILVYN UI 511 -EG\_  
**Lapp code:** Lapp 61797930

The **Test voltage** of the cable Lapp 61797930 is /.

## Application range

- In combination with protective conduit
- SILVYN® UI 511
- Offshore applications
- Outdoors
- Steel industry

## Product Make-up

- Metric connection thread
- Hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 61797930 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	min. internal Ø	Overall length/ C (mm)	Thread length/ D (mm)	Internal Ø	SW (mm)	Suitable for SILVYN® UI 511	Pieces / PU
SILVYN® UI 511 fitting (stainless steel)									
SILVYN UI 511 -EG	Lapp 61797918	M 16 x 1,5/1	6.8	35.0	12.0	6.8	26	5/16"	1.0
SILVYN UI 511 -EG	Lapp 61797920	M 16 x 1,5/2	9.8	35.0	12.0	9.8	26	3/8"	1.0
SILVYN UI 511 -EG	Lapp 61797926	M 20 x 1,5/3	13.9	37.0	13.0	13.9	29	1/2"	1.0
SILVYN UI 511 -EG	Lapp 61797928	M 25 x 1,5	18.5	40.0	15.0	18.5	35	3/4"	1.0
SILVYN UI 511 -EG	Lapp 61797930	M 32 x 1,5	22.8	46.0	15.0	22.8	45	1."	1.0
SILVYN UI 511 -EG	Lapp 61797932	M 40 x 1,5	30.8	52.0	16.0	30.8	54	1 1/4"	1.0